



IPT International Petroleum Trading LTD
Robert-Bosch-Strasse 12
25335 Elmshorn
Company registration number: HRB 13315 PI
Sales tax identification number: DE313987910
E-mailaddress: contact@tippoil.com
Website: www.tippoil.com
Tel: +4923036728527

product certificate

TIPP-OIL CVT KFE (red) 0002-000165

CVT KFE is a fully synthetic automatic transmission lubricant of the latest generation for CVT automatic transmissions. CVT KFE guarantees optimum power transmission. CVT KFE is designed on the basis of fully synthetic oils (PAO) with a special additive and inhibitor which ensure perfect functioning of the automatic transmission.

Application note:

CVT KFE has been developed for use in CVT automatic transmissions (Belt-CVTs and Chain-CVTs). It is not suitable for use in hybrid transmissions with CVT (Toyota Prius, Ford). CVT KFE ensures a stable viscosity even under the highest mechanical stress in the transmission elements (thrust link belt).

Specifications:

Other specifications

Tried and tested in practice in units with filling regulations:

Daihatsu (Amix CVTF-DC / Amix CVTF DFE), Dodge / Jeep (NS-2 / CVTF+4), Ford (CVT23), Ford (CVT30 / Mercon C), G 052180, G 052516, GM/Saturn (DEX-CVT), Honda (HMMF & HFC-2), Hyundai / Kia (SP-III), Hyundai Genuine CVTF, Mercedes Benz (236.20), Mini Cooper

Properties:

Very good lubricating properties even at low temperatures in winter

Very high, stable viscosity index

Very low flow point



IPT International Petroleum Trading LTD
Robert-Bosch-Strasse 12
25335 Elmshorn
Company registration number: HRB 13315 PI
Sales tax identification number: DE313987910
E-mailaddress: contact@tippoil.com
Website: www.tippoil.com
Tel: +4923036728527

Very good oxidation stability

Extensive protection against wear, corrosion and foam formation

Well matched coefficient of friction properties

Neutral behaviour towards sealing materials

Neutral behaviour through inhibition against non-ferrous metals

Properties Data Unit Test according to

Viscosity at 100°C 5,4 MM²/S DIN ISO 51562-2

Viscosity index 201 DIN ISO 2909

Color Red visual

Density at 15°C 832 KG/M³ DIN EN ISO 12185

Pourpoint -54 °C ASTM D 7346

All data given are approximate values and are subject to the usual production fluctuations.

To the best of our knowledge, all data correspond to the current state of knowledge and our development. We reserve the right to make changes. All references to DIN standards are for product description purposes only and do not constitute a guarantee. In case of any problems, please request technical advice.



IPT International Petroleum Trading LTD
Robert-Bosch-Strasse 12
25335 Elmshorn
Company registration number: HRB 13315 PI
Sales tax identification number: DE313987910
E-mailadress: contact@tippoil.com
Website: www.tippoil.com
Tel: +4923036728527

