



IPT International Petroleum Trading LTD  
Robert-Bosch-Strasse 12  
25335 Elmshorn  
Company registration number: HRB 13315 PI  
Sales tax identification number: DE313987910  
**E-mailaddress:** [contact@tippoil.com](mailto:contact@tippoil.com)  
**Website:** [www.tippoil.com](http://www.tippoil.com)  
Tel: +4923036728527

product certificate

TIPP-OIL DCT / DSG Super 0002-000166

DCT / DSG is a synthetic transmission fluid for double clutch transmissions. DCT / DSG ensures a stable lubricating behaviour also under extreme loads in midsummer and low winter temperatures. DCT / DSG enables practically slip-free operation and thus minimum torque losses. DCT / DSG guarantees low wear and a long service life of the gearbox.

Application note:

DCT / DSG Super was specially developed for dual clutch transmissions of various car manufacturers such as Audi, BMW (Getrag), Citroen, Ford/Getrag, Mercedes-Benz, Mitsubishi, Nissan, Peugeot, Porsche, Seat, Skoda, Volkswagen, Volvo.

Specifications:

Other specifications

Tried and tested in practice in units with filling regulation:

BMW 83 22 0 440 214, BMW 83 22 2 147 477, BMW 83 22 2 148 578, BMW 83 22 2 148 579, Ford WSS-M2C936-A, MB 236.21 (001 989 85 03), MZ320065 Dia-Queen SSTF-I, Peugeot/Citroen 9734.S2, Porsche Oil No. 999.917.080.00, VOLVO 1161838/1161839, VW TL 052 182, VW

Very good lubricating properties:

Very good lubricating properties even at low temperatures in winter

Low wear

Excellent viscosity-temperature behaviour

Excellent protection against wear, corrosion and foaming



IPT International Petroleum Trading LTD  
Robert-Bosch-Strasse 12  
25335 Elmshorn  
Company registration number: HRB 13315 PI  
Sales tax identification number: DE313987910  
**E-mailaddress:** [contact@tippoil.com](mailto:contact@tippoil.com)  
**Website:** [www.tippoil.com](http://www.tippoil.com)  
Tel: +4923036728527

Neutral behaviour towards sealing materials

Stable lubricating film even with extreme loads in midsummer

Very low flow point

Properties Data Unit Test according to

Viscosity at 100°C 7.270 MM<sup>2</sup>/S DIN ISO 51562-2

Viscosity index 170 DIN ISO 2909

Colour Yellow visual

Density at 15°C 849.0 KG/M<sup>3</sup> DIN EN ISO 12185

Pourpoint -51 °C ASTM D 7346

All data given are approximate values and are subject to the usual production fluctuations.

To the best of our knowledge, all data correspond to the current state of knowledge and our development. We reserve the right to make changes. All references to DIN standards are for product description purposes only and do not constitute a guarantee. In case of any problems, please request technical advice.



IPT International Petroleum Trading LTD  
Robert-Bosch-Strasse 12  
25335 Elmshorn  
Company registration number: HRB 13315 PI  
Sales tax identification number: DE313987910  
**E-mailadress:** [contact@tippoil.com](mailto:contact@tippoil.com)  
**Website:** [www.tippoil.com](http://www.tippoil.com)  
Tel: +4923036728527

