



IPT International Petroleum Trading LTD  
Robert-Bosch-Strasse 12  
25335 Elmshorn  
Company registration number: HRB 13315 PI  
Sales tax identification number: DE313987910  
**E-mailaddress:** [contact@tippoil.com](mailto:contact@tippoil.com)  
**Website:** [www.tippoil.com](http://www.tippoil.com)  
Tel: +4923036728527

product certificate

TIPP-OIL Dexron III H Colorless 0002-000180

Dexron III H Colorless is designed on the basis of hydrocrack oils and PAO with special additives and inhibitions. Dexron III H Colorless has been specially developed for the specified specifications and applications. Fulfills a maximum of lubrication and wear protection. Dexron III H Colorless is a Universal ATF (Automatic Transmission Fluid) of the latest generation for all automatic transmissions with and without controlled torque converter lock-up clutch (GKÜB) for which transmission fluids of type Dexron III H are prescribed.

Application note:

Dexron III H Colorless is especially suitable for use in gearboxes with ATF Dexron III H specification. It is recommended to rinse with Dexron III H Colorless before final filling with Dexron III H Colorless. The operating instructions of the vehicle and engine manufacturers must be observed.

Specifications:

Other specifications

Tried and tested in practice in units with filling regulations:

Allison C4, TES-389, GM Dexron III H, ATF T-IV, MAN 339 Type Z-2, MB 236.1, 236.6, 236.9, 236.10, VOITH H 55.6336.3x Extended Drain (G1363), VOLVO 1161521/1161511, VOLVO Transmission Oil 97341, ZF TE-ML 04D, 05L, 14B, 16L, 17C

Reliable protection against wear, corrosion and foam formation:

Reliable protection against wear, corrosion and foam formation

High and very stable viscosity index



IPT International Petroleum Trading LTD  
Robert-Bosch-Strasse 12  
25335 Elmshorn  
Company registration number: HRB 13315 PI  
Sales tax identification number: DE313987910  
**E-mailaddress:** [contact@tippoil.com](mailto:contact@tippoil.com)  
**Website:** [www.tippoil.com](http://www.tippoil.com)  
Tel: +4923036728527

Problem-free at very low temperatures

Very low yield point

Very good oxidation stability

Well matched coefficient of friction properties

Neutral behaviour towards sealing materials

Neutral behaviour through inhibition against non-ferrous metals

Properties Data Unit Test according to

Viscosity at 100°C 7.1 MM<sup>2</sup>/S DIN ISO 51562-2

Viscosity index 177 DIN ISO 2909

Colour Yellow visual

Density at 15°C 850 KG/M<sup>3</sup> DIN EN ISO 12185

Pourpoint -51 °C ASTM D 7346

All data given are approximate values and are subject to the usual production fluctuations.

To the best of our knowledge, all data correspond to the current state of knowledge and our development. We reserve the right to make changes. All references to DIN standards are for product description purposes only and do not constitute a guarantee. In case of any problems, please request technical advice.



IPT International Petroleum Trading LTD  
Robert-Bosch-Strasse 12  
25335 Elmshorn  
Company registration number: HRB 13315 PI  
Sales tax identification number: DE313987910  
**E-mailadress:** [contact@tippoil.com](mailto:contact@tippoil.com)  
**Website:** [www.tippoil.com](http://www.tippoil.com)  
Tel: +4923036728527

