



IPT International Petroleum Trading LTD
Robert-Bosch-Strasse 12
25335 Elmshorn
Company registration number: HRB 13315 PI
Sales tax identification number: DE313987910
E-mailaddress: contact@tippoil.com
Website: www.tippoil.com
Tel: +4923036728527

product certificate

TIPP-OIL ATF 8 HP Fluid (green) 0002-000188

ATF 8 HP Fluid (green) is designed on the basis of hydrocrack oils and PAO with a special additive and inhibition, which guarantee a perfect function of the automatic transmission. ATF 8 HP Fluid (green) is an ATF of the latest generation for all 8-speed automatic transmissions and some 6-speed automatic transmissions from ZF. High wear protection is guaranteed in every operating condition.

Application note:

ATF 8 HP Fluid (green) was developed for use in the new 8HP series transmissions of ZF 8HP45, 8HP55, 8HP70, 8HP90 as well as for the 6-speed automatic transmissions of the 6HP series 6HP19X for AUDI Q7, 6HP19A and 6HP28AF. Observe the original part number of the manufacturer.

Specifications:

Other Specifications

Tried and tested in practice in units with filling regulations:

Aisin Warner AW-1, Audi G 055 005, G 055 162, G 052 540, BMW 83 22 0 142 516, BMW 83 22 2 152 426, DSIH 6p805 (Geely, Ssangyong, Mahindra 6sp), Honda DW-1, Hyundai NWS-9638, Hyundai/Kia SP-IV, SPH-IV, SP-IV RR, JASO 1-A-LV, MB 236.12, MB 236.14, MB 236.41

Reliable protection against wear:

Reliable protection against wear, corrosion and foaming

High and stable viscosity index

Good lubricating properties even at low temperatures in winter



IPT International Petroleum Trading LTD
Robert-Bosch-Strasse 12
25335 Elmshorn
Company registration number: HRB 13315 PI
Sales tax identification number: DE313987910
E-mailaddress: contact@tippoil.com
Website: www.tippoil.com
Tel: +4923036728527

Very good oxidation stability

Coordinated coefficient of friction properties

High thermal and oxidative stability

Excellent cooling capacity

Properties Data Unit Test according to

Viscosity at 100°C 5.600 MM²/S DIN ISO 51562-2

Viscosity index 168 DIN ISO 2909

Color Green visual

Density at 15°C 840.0 KG/M³ DIN EN ISO 12185

Pourpoint -51 CELSIUS ASTM D 7346

All data given are approximate values and are subject to the usual production fluctuations.

To the best of our knowledge, all data correspond to the current state of knowledge and our development. We reserve the right to make changes. All references to DIN standards are for product description purposes only and do not constitute a guarantee. In case of any problems, please request technical advice.



IPT International Petroleum Trading LTD
Robert-Bosch-Strasse 12
25335 Elmshorn
Company registration number: HRB 13315 PI
Sales tax identification number: DE313987910
E-mailadress: contact@tippoil.com
Website: www.tippoil.com
Tel: +4923036728527

