



IPT International Petroleum Trading LTD
Robert-Bosch-Strasse 12
25335 Elmshorn
Company registration number: HRB 13315 PI
Sales tax identification number: DE313987910
E-mailaddress: contact@tippoil.com
Website: www.tippoil.com
Tel: +4923036728527

product certificate

TIPP-OIL HVLP 32 0002-000243

Hydraulic HVLP 32 is a multi-grade hydraulic oil developed on the basis of specially selected base oils. Hydraulic HVLP 32 offers high wear protection even under extreme loads due to effective additives. Hydraulic HVLP 32 is particularly characterised by good viscosity and temperature behaviour, high ageing resistance and reliable corrosion protection.

Application note:

Hydraulic HVLP 32 is mainly used in hydraulic systems with strongly fluctuating operating temperatures. Hydraulic HVLP 32 is ideally suited for heavy-duty hydraulic systems, earthmoving machinery and agricultural machinery. It is favoured for strongly fluctuating operating temperatures and must not be used for hydraulic systems containing silver or silver-plated construction and operating elements.

Specifications

Other specifications

Tried and tested in practice in units with filling regulations:

AFNOR 48 603 HV, CETOP RP 91H-HV, DENISON HF-1, HF-0, HF-2, General Motors LH-04-1, General Motors LH-06-1, General Motors LH-15-1, ISO 6743/4-HV, Sperry Vickers 1-286-S, Sperry Vickers M-2950-S, US Steel 127, US Steel 136

Properties:

Reliable protection against corrosion



IPT International Petroleum Trading LTD
Robert-Bosch-Strasse 12
25335 Elmshorn
Company registration number: HRB 13315 PI
Sales tax identification number: DE313987910
E-mailaddress: contact@tippoil.com
Website: www.tippoil.com
Tel: +4923036728527

Excellent wear protection

Stable viscosity index

Good oxidation stability

Good air and water separation capacity thereby preventing foam formation

Very low yield point

Neutral to seals made of plastics

Features & Benefits

Data Unit Test according to

kinematic viscosity at 40°C 29,100 MM²/S DIN ISO 51562-2

Viscosity index 142 DIN ISO 2909

Colour Yellow visual

Density at 15°C 853.0 KG/M³ DIN EN ISO 12185

Pourpoint -27 °C ASTM D 7346

All data are approximate values and are subject to the usual production fluctuations.

To the best of our knowledge and belief, all data correspond to the current state of knowledge and our development. We reserve the right to make changes. All references to DIN standards are for product description purposes only and do not constitute a guarantee. In case of problems please ask for technical advice.

27.07.2018 02:00:12



IPT International Petroleum Trading LTD
Robert-Bosch-Strasse 12
25335 Elmshorn
Company registration number: HRB 13315 PI
Sales tax identification number: DE313987910
E-mailadress: contact@tippoil.com
Website: www.tippoil.com
Tel: +4923036728527

