



IPT International Petroleum Trading LTD
Robert-Bosch-Strasse 12
25335 Elmshorn
Company registration number: HRB 13315 PI
Sales tax identification number: DE313987910
E-mailaddress: contact@tippoil.com
Website: www.tippoil.com
Tel: +4923036728527

product certificate

TIPP-OIL ZHF RL (green) 0002-000262

Description of the

TIPP-OIL ZHF RL (green) is a special hydraulic oil based on synthetic oil with high-quality additives. The properties of ZHF RL (green) are decisively determined by its special formulation. We guarantee excellent cold stability. ZHF RL (green) has optimal performance as central hydraulic oil in power steering, rear axle steering, level control, hydropneumatic suspension, shock absorbers, for active damping and engine support, for hydrostatic drive of fans, alternators and air conditioning, for stability and traction systems (ABS/ASR/ASC), central locking, electrohydraulic convertible top control, hydraulic brake booster and hydropneumatic suspension for VW, Audi, Seat, Skoda. Particularly suitable for use in cold countries.

Application note:

ZHF RL (green) is designed for the application range from -60°C to +130°C and is therefore also recommended for the latest developments on the vehicle market.

Specifications:

DIN 51524 Part 3, ISO 7308

Tried and tested in practice in units with filling regulations:

CHF202, Citroen 9979 A1, Land Rover Cold Climate PAS Fluid 14315 LRN2261, MB 343.0, MB 344.0, MB 345.0, Opel 1940 766, SAAB 93160548, VOLVO 30741424, VW G 004 000



IPT International Petroleum Trading LTD
Robert-Bosch-Strasse 12
25335 Elmshorn
Company registration number: HRB 13315 PI
Sales tax identification number: DE313987910
E-mailaddress: contact@tippoil.com
Website: www.tippoil.com
Tel: +4923036728527

Properties:

Reliable protection against corrosion

Extremely low pour point

Improved viscosity and friction behaviour

Very good wear protection

Excellent thermal stability

Good foaming properties

Neutral behaviour towards sealing materials

Properties Data Unit Test according to

kinematic viscosity at 40°C 20,600 MM²/S DIN ISO 51562-2

Viscosity index 325 DIN ISO 2909

Color Green visual

Density at 15°C 829.0 KG/M³ DIN EN ISO 12185

Pourpoint -72 CELSIUS ASTM D 7346

All data given are approximate values and are subject to the usual production fluctuations.

To the best of our knowledge, all data correspond to the current state of knowledge and our development. We reserve the right to make changes. All references to DIN standards are for product description purposes only and do not constitute a guarantee. In the event of any problems, request technical advice.



IPT International Petroleum Trading LTD
Robert-Bosch-Strasse 12
25335 Elmshorn
Company registration number: HRB 13315 PI
Sales tax identification number: DE313987910
E-mailadress: contact@tippoil.com
Website: www.tippoil.com
Tel: +4923036728527

