



IPT International Petroleum Trading LTD  
Robert-Bosch-Strasse 12  
25335 Elmshorn  
Company registration number: HRB 13315 PI  
Sales tax identification number: DE313987910  
**E-mailaddress:** [contact@tippoil.com](mailto:contact@tippoil.com)  
**Website:** [www.tippoil.com](http://www.tippoil.com)  
Tel: +4923036728527

product certificate

TIP-OIL ATF 6 HP

Description of the

TIPP-OIL ATF 6HP is a synthetic transmission oil based on high-quality hydrocracking oils with a special additive and inhibition that guarantee perfect functioning of the automatic transmission. It is an ATF (Automatic Transmission Fluid) of the latest generation for all ZF 6-speed automatic transmissions and guarantees maximum wear protection in every operating condition.

Instructions for use

TIPP-OIL ATF 6HP was developed for use in ZF's latest 6HP transmissions: 6HP19, 6HP19A, 6HP19X (not for Audi Q7), 6HP21, 6HP21X, 6HP26, 6HP26X, 6HP26A61 (not for Audi W12 engine), 6HP28, 6HP28X, 6HP28A61, 6HP32, 6HP32A, 6HP32X.

It can be used as a replacement for ZF-LIFEGUARDFLUID 6 (ZF No.S671 090 255) outside the warranty period.

Quality Classification

specifications

TIPP-OIL ATF 6 HP is proven in practice and tested in units with filling regulations:

Audi / VW Oil No. G 055005 A1 / A2 / A6

BMW Oil No. 8322 0142516

Jaguar Oil No. Jaguar Fluid 8432



IPT International Petroleum Trading LTD  
Robert-Bosch-Strasse 12  
25335 Elmshorn  
Company registration number: HRB 13315 PI  
Sales tax identification number: DE313987910  
**E-mailaddress:** [contact@tippoil.com](mailto:contact@tippoil.com)  
**Website:** [www.tippoil.com](http://www.tippoil.com)  
Tel: +4923036728527

Maserati Oil No. 231603

AML Oil No. 4G4319A509/AA/S

Bentley Oil No. PY112995PA

Hyundai Oil No. 040000C90SG

Land Rover Oil No. TYK500050

#### Features & Benefits

Reliable protection against wear, corrosion and foam formation

High and very stable viscosity index

Problem-free at very low temperatures

Very low yield point

Very good oxidation stability

Well matched coefficient of friction properties

Neutral behaviour towards sealing materials

Neutral behaviour through inhibition against non-ferrous metals

#### Technical characteristics

Properties Data Unit Test according to

kinematic viscosity at 40°C 29,200 MM<sup>2</sup>/S DIN ISO 51562-2

kinematic viscosity at 100°C 6,000 MM<sup>2</sup>/S DIN ISO 51562-2

viscosity index 154 DIN ISO 2909

appearance YELLOW visual

density at 15°C 844.0 KG/M<sup>3</sup> DIN EN ISO 12185

Pour Point -45 °C ASTM D 7346



IPT International Petroleum Trading LTD  
Robert-Bosch-Strasse 12  
25335 Elmshorn  
Company registration number: HRB 13315 PI  
Sales tax identification number: DE313987910  
**E-mailadress:** [contact@tippoil.com](mailto:contact@tippoil.com)  
**Website:** [www.tippoil.com](http://www.tippoil.com)  
Tel: +4923036728527

All data given are approximate values and are subject to the usual production fluctuations.

To the best of our knowledge, all data correspond to the current state of knowledge and our development. We reserve the right to make changes. All references to DIN standards are for product description purposes only and do not constitute a guarantee. In the event of any problems, request technical advice.

07.09.2018 02:00:04

