



IPT International Petroleum Trading LTD
Robert-Bosch-Strasse 12
25335 Elmshorn
Company registration number: HRB 13315 PI
Sales tax identification number: DE313987910
E-mailaddress: contact@tippoil.com
Website: www.tippoil.com
Tel: +4923036728527

product certificate

TIPP-OIL ATF DX VI Colorless

ATF DX VI Colorless is an automatic transmission oil based on the latest technology in HC/HT hydrocracking oils, approved by General Motors for use in automatic transmission vehicles. The special formulation ensures twice the service life of a comparable ATF oil. ATF DX VI Colorless meets General Motors' transmission oil specifications for all vehicles with Hydramatic automatic transmissions from 2006.

Application note:

ATF DX VI Colorless is fully downward compatible with DEXRON® III (H), III and IIE applications. Always follow the recommendations in your vehicle's owner's manual.

Specifications:

GM DEXRON®-VI

Tried and tested in practice in units with filling regulations:

Aisin Warner AW-1, Aisin Warner JWS 3309 (T-IV) & JWS 3324 (WS), AW-1, Allison C-3 & C-4, American Motors ATF +3 (MS7176-E), ATF +4 (MS9602), ATF+, +2, +3 (MS 7176E), +4 (MS 9602), ATF-Z1, CAT TO-2, Ford MERCON® LV (FF-WSS-M2C-938A/SF, XT-10 QLV), GM DEXR

Good resistance to lubricant failure under harsh operating conditions:

Good resistance to lubricant failure under harsh operating conditions

Outstanding resistance to oil sludge and deposit formation

Superior wear protection, better foaming resistance for smooth shifting as well as

less wear of bearings, bushings and gear wheels



IPT International Petroleum Trading LTD
Robert-Bosch-Strasse 12
25335 Elmshorn
Company registration number: HRB 13315 PI
Sales tax identification number: DE313987910
E-mailaddress: contact@tippoil.com
Website: www.tippoil.com
Tel: +4923036728527

Longer oil life, longer gear life,

Longer replacement intervals

Excellent flowability at low temperatures

Prevention of coupling loops with modulation rotary transducers

Properties Data Unit Test according to

Viscosity at 100°C 5,970 MM²/S DIN ISO 51562-2

Viscosity index 159 DIN ISO 2909

Colour Yellow visual

Density at 15°C 843.6 KG/M³ DIN EN ISO 12185

Pourpoint -51 °C ASTM D 7346

All data given are approximate values and are subject to the usual production fluctuations.

To the best of our knowledge, all data correspond to the current state of knowledge and our development. We reserve the right to make changes. All references to DIN standards are for product description purposes only and do not constitute a guarantee. In case of any problems, please request technical advice.



IPT International Petroleum Trading LTD
Robert-Bosch-Strasse 12
25335 Elmshorn
Company registration number: HRB 13315 PI
Sales tax identification number: DE313987910
E-mailaddress: contact@tippoil.com
Website: www.tippoil.com
Tel: +4923036728527

