



IPT International Petroleum Trading LTD  
Robert-Bosch-Strasse 12  
25335 Elmshorn  
Company registration number: HRB 13315 PI  
Sales tax identification number: DE313987910  
**E-mailaddress:** [contact@tippoil.com](mailto:contact@tippoil.com)  
**Website:** [www.tippoil.com](http://www.tippoil.com)  
Tel: +4923036728527

product certificate

TIPP-OIL ATF DX VI Red

ATF DX VI (red) is an automatic transmission oil based on the latest technology in HC/HT hydrocracking oils, approved by General Motors for use in automatic transmission vehicles. The special formulation ensures twice the life of a comparable ATF oil. ATF DX VI (red) meets General Motors' transmission oil specifications for all vehicles with Hydramatic automatic transmissions from 2006.

Application note:

ATF DX VI (red) is fully downward compatible with DEXRON® III (H), III and IIE applications. Always follow the recommendations in your vehicle's owner's manual.

Specifications:

Ford MERCON® LV (FF-WSS-M2C-938A/SF, XT-10 QLV), GM DEXRON®-VI, JASO M315-2013 1A-LV

Tried and tested in practice in units with filling regulations:

Aisin Warner AW-1, Aisin Warner JWS 3309 (T-IV) & JWS 3324 (WS), AW-1, Allison C-3 & C-4, American Motors ATF +3 (MS7176-E), ATF +4 (MS9602), ATF+, +2, +3 (MS 7176E), +4 (MS 9602), ATF-Z1, CAT TO-2, Honda DW-1, KIA ATF SP-II, SP-III, SP-IV, SP-IVM, Red 1,

Good resistance to lubricant failure under harsh operating conditions:

Good resistance to lubricant failure under harsh operating conditions

Outstanding resistance to oil sludge and deposit formation

Superior wear protection, better foaming resistance for smooth shifting as well as



IPT International Petroleum Trading LTD  
Robert-Bosch-Strasse 12  
25335 Elmshorn  
Company registration number: HRB 13315 PI  
Sales tax identification number: DE313987910  
**E-mailaddress:** [contact@tippoil.com](mailto:contact@tippoil.com)  
**Website:** [www.tippoil.com](http://www.tippoil.com)  
Tel: +4923036728527

less wear of bearings, bushings and gear wheels

Longer oil life, longer gear life,

Longer replacement intervals

Excellent flowability at low temperatures

Prevention of coupling loops with modulation rotary transducers

Properties Data Unit Test according to

Viscosity at 100°C 5,970 MM<sup>2</sup>/S DIN ISO 51562-2

Viscosity index 159 DIN ISO 2909

Color Red visual

Density at 15°C 843.6 KG/M<sup>3</sup> DIN EN ISO 12185

Pourpoint -51 °C ASTM D 7346

All data given are approximate values and are subject to the usual production fluctuations.

To the best of our knowledge, all data correspond to the current state of knowledge and our development. We reserve the right to make changes. All references to DIN standards are for product description purposes only and do not constitute a guarantee. In case of any problems, please request technical advice.



IPT International Petroleum Trading LTD  
Robert-Bosch-Strasse 12  
25335 Elmshorn  
Company registration number: HRB 13315 PI  
Sales tax identification number: DE313987910  
**E-mailaddress:** [contact@tippoil.com](mailto:contact@tippoil.com)  
**Website:** [www.tippoil.com](http://www.tippoil.com)  
Tel: +4923036728527

