



IPT International Petroleum Trading LTD
Robert-Bosch-Strasse 12
25335 Elmshorn
Company registration number: HRB 13315 PI
Sales tax identification number: DE313987910
E-mailaddress: contact@tippoil.com
Website: www.tippoil.com
Tel: +4923036728527

product certificate

TIPP-OIL ATF MB-9 Red

ATF MB-9 (red) is an oil for automatic transmissions based on synthetic oils. ATF MB-9 (red) has been specially developed for the specified specifications and applications. Fulfills a maximum of lubrication and wear protection through special additives. ATF MB-9 (red) is a Universal ATF (Automatic Transmission Fluid) of the latest generation for all automatic transmissions with and without controlled torque converter lock-up clutch (GKÜB = transmission-clutch lock-up).

Application note:

ATF MB-9 (red) is particularly suitable for use in modern Mercedes Benz 7-speed automatic transmissions. It enables a maximum of wear protection in every operating condition. The operating instructions of the vehicle and engine manufacturers must be observed.

Specifications:

Allison C-4, JASO 1-A, Voith H55.6335

Tried and tested in practice in units with filling regulations:

Allison TES 389B, TES-295; MAN 339F, Audi G 052 162 / G 052 990 / G 055 025, ETL-7045E, ETL-8072B (BMW 5 Sp), Ford M; GM-IID / IIIG / IIHH; Honda ATF Z-1, Ford M2C195-A; GM P/N 89021184, Ford Part # XL-12; GM AutoTrak II, GM P/N 12345866 (GM 9985835); Hyu

Very good lubricating properties:

Very good lubricating properties even at low temperatures in winter

high, stable viscosity index

Very low flow point



IPT International Petroleum Trading LTD
Robert-Bosch-Strasse 12
25335 Elmshorn
Company registration number: HRB 13315 PI
Sales tax identification number: DE313987910
E-mailadress: contact@tippoil.com
Website: www.tippoil.com
Tel: +4923036728527

Very good oxidation stability

Extensive protection against wear, corrosion and foam formation

Excellent coefficient of friction stability

High thermal and oxidative stability

Excellent cooling capacity.

Excellent shear stability

Lowest evaporation losses

Neutral behaviour towards sealing materials

Neutral behaviour through inhibition against non-ferrous metals

Properties Data Unit Test according to

Viscosity at 100°C 7.261 MM²/S DIN ISO 51562-2

Viscosity index 153 DIN ISO 2909

Color Red visual

Density at 15°C 846.6 KG/M³ DIN EN ISO 12185

Pourpoint -45 °C ASTM D 7346

All data given are approximate values and are subject to the usual production fluctuations.

To the best of our knowledge, all data correspond to the current state of knowledge and our development. We reserve the right to make changes. All references to DIN standards are for product description purposes only and do not constitute a guarantee. In case of any problems, please request technical advice.



IPT International Petroleum Trading LTD
Robert-Bosch-Strasse 12
25335 Elmshorn
Company registration number: HRB 13315 PI
Sales tax identification number: DE313987910
E-mailaddress: contact@tippoil.com
Website: www.tippoil.com
Tel: +4923036728527

