



IPT International Petroleum Trading LTD  
Robert-Bosch-Strasse 12  
25335 Elmshorn  
Company registration number: HRB 13315 PI  
Sales tax identification number: DE313987910  
**E-mailaddress:** [contact@tippoil.com](mailto:contact@tippoil.com)  
**Website:** [www.tippoil.com](http://www.tippoil.com)  
Tel: +4923036728527

product certificate

TIPP-OIL Central hydraulic fluid 0002-000257

Description of the

TIPP-OIL Central Hydraulic Fluid is a special hydraulic oil based on synthetic and mineral oil with high-quality additives. Due to its special formulation, the properties of Central Hydraulic Fluid are decisively determined. We guarantee excellent cold stability. Central Hydraulic Fluid has an optimal performance as central hydraulic oil in power steering, rear axle steering, level control, hydropneumatic suspension, shock absorbers, for active damping and engine support, for hydrostatic drive of fan, alternator and air conditioning, for stability and traction systems (ABS/ASR/ASC), central locking, electrohydraulic convertible top control, hydraulic brake booster and hydropneumatic suspension for VW, Audi, Seat, Skoda. Particularly suitable for use in cold countries.

Application note:

Central Hydraulic Fluid is designed for the application range from -60°C to +130°C and is therefore also recommended for the latest developments on the vehicle market.

Specifications:

DIN 51524 Part 2

Tried and tested in practice in units with filling regulations:

CHF202, Citroen 9979 A1, Land Rover Cold Climate PAS Fluid 14315 LRN2261, MB 343.0, Opel 1940 766, SAAB 93160548, VOLVO 30741424, VW G 004 000



IPT International Petroleum Trading LTD  
Robert-Bosch-Strasse 12  
25335 Elmshorn  
Company registration number: HRB 13315 PI  
Sales tax identification number: DE313987910  
**E-mailaddress:** [contact@tippoil.com](mailto:contact@tippoil.com)  
**Website:** [www.tippoil.com](http://www.tippoil.com)  
Tel: +4923036728527

Properties:

Reliable protection against corrosion

Extremely low pour point

Improved viscosity and friction behaviour

Very good wear protection

Excellent thermal stability

Good foaming properties

Neutral behaviour towards sealing materials

Properties Data Unit Test according to

kinematic viscosity at 40°C 25.300 MM<sup>2</sup>/S DIN ISO 51562-2

Viscosity index 267 DIN ISO 2909

Color Green visual

Density at 15°C 845.0 KG/M<sup>3</sup> DIN EN ISO 12185

Pourpoint -60 CELSIUS ASTM D 7346

All data given are approximate values and are subject to the usual production fluctuations.

To the best of our knowledge, all data correspond to the current state of knowledge and our development. We reserve the right to make changes. All references to DIN standards are for product description purposes only and do not constitute a guarantee. In the event of any problems, request technical advice.



IPT International Petroleum Trading LTD  
Robert-Bosch-Strasse 12  
25335 Elmshorn  
Company registration number: HRB 13315 PI  
Sales tax identification number: DE313987910  
**E-mailaddress:** [contact@tippoil.com](mailto:contact@tippoil.com)  
**Website:** [www.tippoil.com](http://www.tippoil.com)  
Tel: +4923036728527

