



IPT International Petroleum Trading LTD  
Robert-Bosch-Strasse 12  
25335 Elmshorn  
Company registration number: HRB 13315 PI  
Sales tax identification number: DE313987910  
**E-mailaddress:** [contact@tippoil.com](mailto:contact@tippoil.com)  
**Website:** [www.tippoil.com](http://www.tippoil.com)  
Tel: +4923036728527

product certificate

TIPP-OIL Classic 30 SB

Description of the

TIPP-OIL Classic 30 SB with its unique formulation extend the service life of the engine in older vehicles by protecting it from silting up and wear. The minimization of friction also reduces fuel consumption.

TIPP-OIL Classic 30 SB is an alloyed monograde oil for use in classic vehicles with and without oil filter. Manufactured from carefully selected, pure mineral refinements with selected additives. TIPP-OIL Classic 30 SB is oxidation stable, non-foaming and has excellent viscosity-temperature behaviour. Due to its low pour point, this oil can be used at both low and high temperatures and guarantees perfect lubrication. It is suitable for use in most petrol-powered vehicle engines and classic vehicles built before 1951. Use in modern engines can lead to poor performance or cause damage.

Instructions for use

TIPP-OIL Classic 30 SB is used in engines of vehicles built up to 1951 if the API specification SB is required.

Observe oil change intervals according to manufacturer's instructions.

Quality Classification

specifications

API SB



IPT International Petroleum Trading LTD  
Robert-Bosch-Strasse 12  
25335 Elmshorn  
Company registration number: HRB 13315 PI  
Sales tax identification number: DE313987910  
**E-mailaddress:** [contact@tippoil.com](mailto:contact@tippoil.com)  
**Website:** [www.tippoil.com](http://www.tippoil.com)  
Tel: +4923036728527

TIPP-OIL Classic 30 SB is proven in practice and tested in units with filling regulations:

-

#### Features & Benefits

excellent material compatibility  
prevents varnishing and coking of cylinders, pistons and valves  
high oxidation protection due to selected base oils  
Safe lubricating film at high operating temperatures  
Neutrality towards sealing materials  
Excellent protection against wear, corrosion and foam formation.

#### Technical characteristics

Properties Data Unit Test according to  
kinematic viscosity at 100°C 11.38 MM<sup>2</sup>/S DIN ISO 51562-2  
viscosity index 96 DIN ISO 2909  
appearance YELLOW visual  
density at 15°C 879,6 KG/M<sup>3</sup> DIN EN ISO 12185  
Pour Point -12 °C ASTM D 7346

All data given are approximate values and are subject to the usual production fluctuations.

To the best of our knowledge, all data correspond to the current state of knowledge and our development. We reserve the right to make changes. All references to DIN standards are for product description purposes only and do not constitute a guarantee. In the event of any problems, request technical advice.

04.07.2018 11:52:03



IPT International Petroleum Trading LTD  
Robert-Bosch-Strasse 12  
25335 Elmshorn  
Company registration number: HRB 13315 PI  
Sales tax identification number: DE313987910  
**E-mailaddress:** [contact@tippoil.com](mailto:contact@tippoil.com)  
**Website:** [www.tippoil.com](http://www.tippoil.com)  
Tel: +4923036728527

