



IPT International Petroleum Trading LTD
Robert-Bosch-Strasse 12
25335 Elmshorn
Company registration number: HRB 13315 PI
Sales tax identification number: DE313987910
E-mailadress: contact@tippoil.com
Website: www.tippoil.com
Tel: +4923036728527

product certificate

TIPP-OIL Classic SAE SC 20W-50

Description of the

TIPP-OIL Classic SAE SC 20W-50 is a mildly alloyed year-round engine oil, the composition of which has been specially adapted to the requirements of classic and youngtimer vehicles with oil filters. Suitable for petrol and diesel engines, which were developed for multi-grade oils of their time.

TIPP-OIL Classic SAE SC 20W-50 extends engine life by increasing the concentration of zinc. This reduces deposits, wear and leaks. The special viscosity ensures stable oil pressure and optimum compression even at high temperatures.

Instructions for use

TIPP-OIL Classic SAE SC 20W-50 Especially suitable for classic vehicles with oil filter elements built after 1950 in which a mild alloyed lubricant is required.

TIPP-OIL Classic SAE SC 20W-50 Also suitable for older construction machinery engines as well as for older circulation lubrication systems and hydrostatic drives.

Quality Classification

Specifications API SC

TIPP-OIL Classic SAE SC 20W-50 has been tried and tested in practice in units with filling regulations:

-



IPT International Petroleum Trading LTD
Robert-Bosch-Strasse 12
25335 Elmshorn
Company registration number: HRB 13315 PI
Sales tax identification number: DE313987910
E-mailadress: contact@tippoil.com
Website: www.tippoil.com
Tel: +4923036728527

Features & Benefits

excellent material compatibility
prevents varnishing and coking of cylinders, pistons and valves
high oxidation protection due to selected base oils
Safe lubricating film at high operating temperatures
Neutrality towards sealing materials
high zinc content for reliable wear protection
Excellent protection against wear, corrosion and foam formation.

Technical characteristics

Properties Data Unit Test according to
kinematic viscosity at 100°C 18.75 MM²/S DIN ISO 51562-2
viscosity index 123 DIN ISO 2909
visual appearance YELLOWBROWN
density at 15°C 881,5 KG/M³ DIN EN ISO 12185
Pour Point -27 °C ASTM D 7346

All data given are approximate values and are subject to the usual production fluctuations.

To the best of our knowledge, all data correspond to the current state of knowledge and our development. We reserve the right to make changes. All references to DIN standards are for product description purposes only and do not constitute a guarantee. In the event of any problems, request technical advice.

04.07.2018 11:52:06



IPT International Petroleum Trading LTD
Robert-Bosch-Strasse 12
25335 Elmshorn
Company registration number: HRB 13315 PI
Sales tax identification number: DE313987910
E-mailadress: contact@tippoil.com
Website: www.tippoil.com
Tel: +4923036728527

