



IPT International Petroleum Trading LTD  
Robert-Bosch-Strasse 12  
25335 Elmshorn  
Company registration number: HRB 13315 PI  
Sales tax identification number: DE313987910  
**E-mailaddress:** [contact@tippoil.com](mailto:contact@tippoil.com)  
**Website:** [www.tippoil.com](http://www.tippoil.com)  
Tel: +4923036728527

product certificate

TIPP-OIL Classic SAE SE 20W-50

Description of the

excellent material compatibility prevents varnishing and coking of cylinders, pistons and valves high oxidation protection through selected base oils safe lubricating film at high operating temperatures neutrality towards sealing materials high zinc content for safe wear protection

Excellent protection against wear, corrosion and foam formation.

TIPP-OIL Classic SAE SE 20W-50 is a mildly alloyed year-round engine oil, the composition of which has been specially adapted to the requirements of vintage and youngtimer vehicles with oil filters. Suitable for petrol and diesel engines, which were developed for multi-grade oils of their time.

TIPP-OIL Classic SAE SE 20W-50 extends engine life by increasing the concentration of zinc. This reduces deposits, wear and leaks. The special viscosity ensures stable oil pressure and optimum compression even at high temperatures.

Instructions for use

TIPP-OIL Classic SAE SE 20W-50 Specially suitable for classic vehicles with oil filter elements built after 1950 in which a mild alloyed lubricant is required.

TIPP-OIL Classic SAE SE 20W-50 is also suitable for older construction machinery engines as well as for older circulation lubrication systems and hydrostatic drives.

Quality Classification

Specifications API SE



IPT International Petroleum Trading LTD  
Robert-Bosch-Strasse 12  
25335 Elmshorn  
Company registration number: HRB 13315 PI  
Sales tax identification number: DE313987910  
**E-mailadress:** [contact@tippoil.com](mailto:contact@tippoil.com)  
**Website:** [www.tippoil.com](http://www.tippoil.com)  
Tel: +4923036728527

TIPP-OIL Classic SAE SE 20W-50 is field-proven and tested in units with filling regulations:

-

#### Features & Benefits

#### Technical characteristics

Properties Data Unit Test according to

kinematic viscosity at 100°C 18.92 MM<sup>2</sup>/S DIN ISO 51562-2

viscosity index 123 DIN ISO 2909

visual appearance YELLOWBROWN

density at 15°C 881,7 KG/M<sup>3</sup> DIN EN ISO 12185

Pour Point -27 °C ASTM D 7346

All data given are approximate values and are subject to the usual production fluctuations.

To the best of our knowledge, all data correspond to the current state of knowledge and our development. We reserve the right to make changes without notice. All references to DIN standards are for product description purposes only and do not constitute a guarantee. In the event of any problems, request technical advice.

04.07.2018 11:52:09



IPT International Petroleum Trading LTD  
Robert-Bosch-Strasse 12  
25335 Elmshorn  
Company registration number: HRB 13315 PI  
Sales tax identification number: DE313987910  
**E-mailaddress:** [contact@tippoil.com](mailto:contact@tippoil.com)  
**Website:** [www.tippoil.com](http://www.tippoil.com)  
Tel: +4923036728527

