



IPT International Petroleum Trading LTD
Robert-Bosch-Strasse 12
25335 Elmshorn
Company registration number: HRB 13315 PI
Sales tax identification number: DE313987910
E-mailaddress: contact@tippoil.com
Website: www.tippoil.com
Tel: +4923036728527

product certificate

TIPP-OIL Combi Pro 5W-30

Description of the

TIPP-OIL Combi Pro 5W-30 is a synthetic low-viscosity engine oil for modern passenger car gasoline and diesel engines with and without turbocharging and direct injection.

TIPP-OIL Combi Pro 5W-30 is characterized by minimized fuel consumption, offers excellent oil supply during cold starts and ensures high wear and corrosion protection.

Extended oil change intervals according to manufacturer's instructions.

Instructions for use

TIPP-OIL Combi Pro 5W-30 is ideally suited for energy-saving year-round use in all modern passenger car petrol and diesel engines.

TIPP-OIL Combi Pro 5W-30 extends the service life of diesel particulate filters. The operating instructions of the vehicle and engine manufacturers must be observed.

Quality Classification

specifications

API SN ACEA C3

TIPP-OIL Combi Pro 5W-30 is field-proven and tested in units with filling regulations:

BMW Longlife-04

MB 229.51/229.31

Fiat 9.55535-S3

Porsche C30



IPT International Petroleum Trading LTD
Robert-Bosch-Strasse 12
25335 Elmshorn
Company registration number: HRB 13315 PI
Sales tax identification number: DE313987910
E-mailaddress: contact@tippoil.com
Website: www.tippoil.com
Tel: +4923036728527

VW 504 00/507 00

Features & Benefits

Excellent cold start properties

Very stable and excellent viscosity behaviour even at high speeds, high shear stability

Fuel savings under all operating conditions

Neutrality towards sealing materials

Low evaporation tendency, thus low oil consumption

catalyst suitability

Extended oil change intervals protect natural resources

Technical characteristics

Properties Data Unit Test according to

kinematic viscosity at 40°C 70.2 MM²/S DIN ISO 51562-2

kinematic viscosity at 100°C 12.0 MM²/S DIN ISO 51562-2

viscosity index 169 DIN ISO 2909

visual appearance YELLOWBROWN

density at 15°C 849 KG/M³ DIN EN ISO 12185

Pour Point -42 CELSIUS ASTM D 7346

All data given are approximate values and are subject to the usual production fluctuations.

To the best of our knowledge, all data correspond to the current state of knowledge and our development. We reserve the right to make changes. All references to DIN standards are for product description purposes only and do not constitute a guarantee. In the event of any problems, request technical advice. 13.07.2018 02:00:40



IPT International Petroleum Trading LTD
Robert-Bosch-Strasse 12
25335 Elmshorn
Company registration number: HRB 13315 PI
Sales tax identification number: DE313987910
E-mailaddress: contact@tippoil.com
Website: www.tippoil.com
Tel: +4923036728527

