



IPT International Petroleum Trading LTD
Robert-Bosch-Strasse 12
25335 Elmshorn
Company registration number: HRB 13315 PI
Sales tax identification number: DE313987910
E-mailaddress: contact@tippoil.com
Website: www.tippoil.com
Tel: +4923036728527

product certificate

TIPP-OIL DXS Premium 0W-20

Description of the

TIPP-OIL DXS 0W-20 is a synthetic Mid SAPS low-viscosity engine oil for passenger car gasoline and diesel engines with and without turbocharging and direct injection.

It prevents premature fuel ignition LSPI (Low Speed Pre Ignition),

Engine damage is thus avoided

TIPP-OIL DXS 0W-20 is characterized by excellent cold start properties, minimization of fuel consumption, friction and wear.

Extended oil change intervals according to manufacturer's instructions.

Instructions for use

TIPP-OIL DXS 0W-20 is ideally suited for energy-saving year-round use in modern passenger car petrol and diesel engines. It is recommended for Opel and General Motors passenger car engines according to Dexos 1 specification under all operating conditions.

The operating instructions of the vehicle and engine manufacturers must be observed.

Quality Classification

specifications

API SN (RC)

API SN Plus



IPT International Petroleum Trading LTD
Robert-Bosch-Strasse 12
25335 Elmshorn
Company registration number: HRB 13315 PI
Sales tax identification number: DE313987910
E-mailaddress: contact@tippoil.com
Website: www.tippoil.com
Tel: +4923036728527

Recommendation.

ILSAC GF-5 ILSAC GF-5

Licensed. API SN (RC) API SN (RC) Licensed: ILSAC GF-5

Licensed: API SN Plus

TIPP-OIL DXS Premium 0W-20 is proven in practice and tested in units with filling regulations:

dexos1Gen 2

Fiat 9.55535-GSX/CR1

Chrysler MS-6395

GM 6094M

Ford WSS-M2C947-A

Features & Benefits

A very stable and excellent viscosity behaviour, shear stability

Fuel savings under all operating conditions

Very good detergent and dispersing properties

Neutrality towards sealing materials

Excellent protection against wear, corrosion and foam formation.

Catalyst suitability

High oxidation stability

A reliable lubricating film at very high operating temperatures

Very good cold start properties



IPT International Petroleum Trading LTD
Robert-Bosch-Strasse 12
25335 Elmshorn
Company registration number: HRB 13315 PI
Sales tax identification number: DE313987910
E-mailaddress: contact@tippoil.com
Website: www.tippoil.com
Tel: +4923036728527

Technical characteristics

Properties Data Unit Test according to

kinematic viscosity at 40°C 44.5 MM²/S DIN ISO 51562-2

kinematic viscosity at 100°C 8.3 MM²/S DIN ISO 51562-2

viscosity index 164 DIN ISO 2909

appearance YELLOW visual

density at 15°C 846 KG/M³ DIN EN ISO 12185

Pour Point -39 CELSIUS ASTM D 7346

total base number 8.7 ASTM D 2896

All data given are approximate values and are subject to the usual production fluctuations.

To the best of our knowledge, all data correspond to the current state of knowledge and our development. We reserve the right to make changes. All references to DIN standards are for product description purposes only and do not constitute a guarantee. In case of any problems, please request technical advice.

23.07.2018 02:00:40

