



IPT International Petroleum Trading LTD  
Robert-Bosch-Strasse 12  
25335 Elmshorn  
Company registration number: HRB 13315 PI  
Sales tax identification number: DE313987910  
**E-mailaddress:** [contact@tippoil.com](mailto:contact@tippoil.com)  
**Website:** [www.tippoil.com](http://www.tippoil.com)  
Tel: +4923036728527

product certificate

TIPP-OIL Dexron D II (red) ATF

Dexron D II is a very high quality transmission fluid for automatic transmissions of all vehicles and machines. Dexron D II is manufactured on the basis of highly refined mineral oils with appropriate additives. It has been specially developed for the specified specifications and applications. Dexron D II fulfils a maximum of lubrication and wear protection through special additives.

Application note:

Dexron D II was developed for use in automatic transmissions, hydraulic steering systems, converters and power transmissions and can be used as a universal ATF (Automatic Transmission Fluid) for all vehicles and machines. A Dexron D II is recommended when a Dexron DII type ATF is to be used in accordance with the manufacturer's specifications. The operating instructions of the vehicle and engine manufacturers must be observed.

Specifications:

Ford Mercon, GM Dexron D II

Tried and tested in practice in units with filling regulations:

Caterpillar TO-2, Ford SQM-9010B, M2C-138 CJ, 166H, 185A, MAN 339 Type Z-1, MB 236.6, 236.7, Renk Doromat, VOITH 55.6335.xx, ZF TE-ML 03D, 04D, 11A, 14A, 17C, 05L

Properties. Reliable protection against wear, mud, adhesions and corrosion:

Reliable protection against wear, sludge, adhesions and corrosion

Stable and excellent viscosity-temperature behaviour



IPT International Petroleum Trading LTD  
Robert-Bosch-Strasse 12  
25335 Elmshorn  
Company registration number: HRB 13315 PI  
Sales tax identification number: DE313987910  
**E-mailaddress:** [contact@tippoil.com](mailto:contact@tippoil.com)  
**Website:** [www.tippoil.com](http://www.tippoil.com)  
Tel: +4923036728527

Problem-free at both very low and very high temperatures

Foam-free even under the heaviest loads

Thermally extraordinarily high load-bearing capacity

Miscible and compatible with all brand ATF's

Neutral behaviour towards sealing materials

Properties Data Unit Test according to

Viscosity at 100°C 7,200 MM<sup>2</sup>/S DIN ISO 51562-2

Viscosity index 167 DIN ISO 2909

Color Red visual

Density at 15°C 852.0 KG/M<sup>3</sup> DIN EN ISO 12185

Pourpoint -48 CELSIUS ASTM D 7346

All data given are approximate values and are subject to the usual production fluctuations.

To the best of our knowledge, all data correspond to the current state of knowledge and our development. We reserve the right to make changes. All references to DIN standards are for product description purposes only and do not constitute a guarantee. In case of any problems, please request technical advice.



IPT International Petroleum Trading LTD  
Robert-Bosch-Strasse 12  
25335 Elmshorn  
Company registration number: HRB 13315 PI  
Sales tax identification number: DE313987910  
**E-mailadress:** [contact@tippoil.com](mailto:contact@tippoil.com)  
**Website:** [www.tippoil.com](http://www.tippoil.com)  
Tel: +4923036728527

