



IPT International Petroleum Trading LTD
Robert-Bosch-Strasse 12
25335 Elmshorn
Company registration number: HRB 13315 PI
Sales tax identification number: DE313987910
E-mailaddress: contact@tippoil.com
Website: www.tippoil.com
Tel: +4923036728527

product certificate

TIPP-OIL Dexron III H Red ATF

Dexron III H is designed on the basis of hydrocrack oils and PAO with a special additive and inhibition. Dexron III H has been specially developed for the specified specifications and applications. Fulfills a maximum of lubrication and wear protection by special additives. Dexron III H is a Universal ATF (Automatic Transmission Fluid) of the latest generation for all automatic transmissions with and without controlled torque converter lock-up clutch (GKÜB) for which Dexron III H transmission fluids are specified.

Application note:

Dexron III H is especially suitable for use in transmissions with ATF Dexron III H regulations. AVENO Dexron III H is miscible with all ATF's brands. It is recommended to rinse with Dexron III H before, rather the final filling with Dexron III H is made. The operating instructions of the vehicle and engine manufacturers must be observed.

Specifications:

Other specifications

Tried and tested in practice in units with filling regulations:

Allison C4, TES-389, GM Dexron III H, ATF T-IV, MAN 339 Type Z-2, MB 236.1, 236.6, 236.9, 236.10, VOITH H 55.6336.3x Extended Drain (G1363), VOLVO 1161521/1161511, VOLVO Transmission Oil 97341, ZF TE-ML 04D, 05L, 14B, 16L, 17C



IPT International Petroleum Trading LTD
Robert-Bosch-Strasse 12
25335 Elmshorn
Company registration number: HRB 13315 PI
Sales tax identification number: DE313987910
E-mailaddress: contact@tippoil.com
Website: www.tippoil.com
Tel: +4923036728527

Properties:

Reliable protection against wear, corrosion and foam formation
High and very stable viscosity index
Problem-free at very low temperatures
Very low yield point
Very good oxidation stability
Well matched coefficient of friction properties
Neutral behaviour towards sealing materials
Neutral behaviour

Properties Data Unit Test according to

Viscosity at 100°C 7.1 MM²/S DIN ISO 51562-2
Viscosity index 177 DIN ISO 2909
Color Red visual
Density at 15°C 850 KG/M³ DIN EN ISO 12185
Pourpoint -51 °C ASTM D 7346

All data are approximate values and are subject to the usual production fluctuations.

To the best of our knowledge and belief, all data correspond to the current state of knowledge and our development. We reserve the right to make changes. All references to DIN standards are for product description purposes only and do not constitute a guarantee. In case of problems please ask for technical advice.

27.07.2018 02:00:12



IPT International Petroleum Trading LTD
Robert-Bosch-Strasse 12
25335 Elmshorn
Company registration number: HRB 13315 PI
Sales tax identification number: DE313987910
E-mailaddress: contact@tippoil.com
Website: www.tippoil.com
Tel: +4923036728527

