



IPT International Petroleum Trading LTD  
Robert-Bosch-Strasse 12  
25335 Elmshorn  
Company registration number: HRB 13315 PI  
Sales tax identification number: DE313987910  
**E-mailaddress:** [contact@tippoil.com](mailto:contact@tippoil.com)  
**Website:** [www.tippoil.com](http://www.tippoil.com)  
Tel: +4923036728527

product certificate

TIPP-OIL FS Dura Fusion 5W-40

Description of the

TIPP-OIL FS Dura Fusion 5W-40 is a synthetic low SAPS fuel-efficient engine oil for passenger cars, gasoline and diesel engines.

Diesel engines. It is suitable for modern diesel engines with particulate filter. TIPP-OIL FS Dura Fusion

5W-40 is characterized by excellent cold start characteristics, minimization of

fuel consumption, friction and wear. It helps to protect the environment. Extended oil change intervals according to manufacturer's instructions.

Instructions for use

TIPP-OIL FS Dura Fusion 5W-40 is a synthetic low friction engine oil, which was developed especially for diesel engines with particle filter.

Quality Classification

specifications

ACEA C4

TIPP-OIL FS Dura Fusion 5W-40 is field-proven and tested in units with filling regulations:

MB 229.51/226.51 Renault RN0720



IPT International Petroleum Trading LTD  
Robert-Bosch-Strasse 12  
25335 Elmshorn  
Company registration number: HRB 13315 PI  
Sales tax identification number: DE313987910  
**E-mailaddress:** [contact@tippoil.com](mailto:contact@tippoil.com)  
**Website:** [www.tippoil.com](http://www.tippoil.com)  
Tel: +4923036728527

#### Features & Benefits

Excellent cold start properties even at low temperatures below -30°C  
The function of the hydraulic plungers is guaranteed at all temperatures.  
Fuel savings under all operating conditions  
A safe lubricating film at high operating temperatures  
Neutrality towards sealing materials  
Extensive protection against wear, corrosion and foam formation.  
Low tendency to evaporation, thus low oil consumption.  
Extended oil change intervals protect natural resources  
Low SAPS = reduced sulfated ash, phosphorus and sulfur

#### Technical characteristics

Properties Data Unit Test according to  
kinematic viscosity at 40°C 80.8 MM<sup>2</sup>/S DIN ISO 51562-2  
kinematic viscosity at 100°C 13.3 MM<sup>2</sup>/S DIN ISO 51562-2  
viscosity index 168 DIN ISO 2909  
visual appearance YELLOWBROWN  
density at 15°C 848 KG/M<sup>3</sup> DIN EN ISO 12185  
Pour Point -39 °C ASTM D 7346

All data given are approximate values and are subject to the usual production fluctuations.  
To the best of our knowledge, all data correspond to the current state of knowledge and our development. We reserve the right to make changes. All references to DIN standards are for product description purposes only and do not constitute a guarantee. In the event of any problems, request technical advice.23.07.2018 02:00:39



IPT International Petroleum Trading LTD  
Robert-Bosch-Strasse 12  
25335 Elmshorn  
Company registration number: HRB 13315 PI  
Sales tax identification number: DE313987910  
**E-mailaddress:** [contact@tippoil.com](mailto:contact@tippoil.com)  
**Website:** [www.tippoil.com](http://www.tippoil.com)  
Tel: +4923036728527

