



IPT International Petroleum Trading LTD
Robert-Bosch-Strasse 12
25335 Elmshorn
Company registration number: HRB 13315 PI
Sales tax identification number: DE313987910
E-mailaddress: contact@tippoil.com
Website: www.tippoil.com
Tel: +4923036728527

product certificate

TIPP-OIL Eco Power 5W-30

Description of the

TIPP OIL ECO Power 5W-30 is ideally suited for energy-saving year-round use in modern passenger car gasoline and diesel engines. The product's application range is extended by the fact that the API SN-RC and ILSAC GF-5 specifications are backward compatible with the previous specifications. These specifications are relevant for many manufacturers as a basic specification for their own specifications or directly as a specification for the application. This affects Asian manufacturers such as Nissan, Subaru and Toyota as well as American manufacturers such as Ford, Chrysler and Lexus. The operating instructions of the vehicle and engine manufacturers must be observed.

Instructions for use

TIPP OIL ECO Power 5W-30 is a semi-synthetic low-viscosity engine oil with trend-setting additives for petrol and diesel engines for passenger cars with and without turbocharging and direct injection. Friction, wear and fuel consumption are reduced and it is characterized by excellent cold start properties. The excellent cold-start behaviour ensures optimum lubrication reliability in the cold-start phase. TIPP OIL ECO Power 5W-30 contributes to the protection of our environment by reducing emissions through noticeable fuel savings. Extended oil change intervals according to manufacturer's instructions.

Quality Classification

specifications

ILSAC GF-5 API SN (RC)

TIPP-OIL Eco Power 5W-30 is proven in practice and tested in units with filling regulations:



IPT International Petroleum Trading LTD
Robert-Bosch-Strasse 12
25335 Elmshorn
Company registration number: HRB 13315 PI
Sales tax identification number: DE313987910
E-mailadress: contact@tippoil.com
Website: www.tippoil.com
Tel: +4923036728527

Chrysler MS-6395, Fiat 9.55535-CR1, Ford WSS-M2C929-A, Ford WSS-M2C946-A, GM 6094M

Eigenschaften

- Excellent cold start properties even at low temperatures
- Fuel savings under all operating conditions
- Very good detergent and dispersing properties
- Neutrality towards sealing materials
- Low evaporation tendency, thus low oil consumption
- Extensive protection against wear, corrosion and foam formation
- Extended oil change intervals protect natural resources

Technical characteristics

Properties Data Unit Test according to

kinematic viscosity at 40°C 56.6 MM²/S DIN ISO 51562-2

kinematic viscosity at 100°C 9.8 MM²/S DIN ISO 51562-2

viscosity index 160 DIN ISO 2909

visual appearance YELLOWBROWN

density at 15°C 854 KG/M³ DIN EN ISO 12185

Pour Point -39 °C ASTM D 7346



IPT International Petroleum Trading LTD
Robert-Bosch-Strasse 12
25335 Elmshorn
Company registration number: HRB 13315 PI
Sales tax identification number: DE313987910
E-mailaddress: contact@tippoil.com
Website: www.tippoil.com
Tel: +4923036728527

All data given are approximate values and are subject to the usual production fluctuations.

To the best of our knowledge, all data correspond to the current state of knowledge and our development. We reserve the right to make changes. All references to DIN standards are for product description purposes only and do not constitute a guarantee. In case of any problems, please request technical advice.

17.07.2018 02:01:00

