



IPT International Petroleum Trading LTD  
Robert-Bosch-Strasse 12  
25335 Elmshorn  
Company registration number: HRB 13315 PI  
Sales tax identification number: DE313987910  
**E-mailadress:** [contact@tippoil.com](mailto:contact@tippoil.com)  
**Website:** [www.tippoil.com](http://www.tippoil.com)  
Tel: +4923036728527

product certificate

TIPP-OIL Excellence 5W-30

Description of the

TIPP-OIL Excellence 5W-30 is a synthetic low-viscosity engine oil for passenger car gasoline and diesel engines with and without turbocharging and direct injection.

TIPP-OIL Excellence 5W-30 is characterized by excellent cold start properties, minimization of fuel consumption, friction and wear.

TIPP-OIL Excellence 5W-30 is an engine oil specially developed for the requirements of Ford and Renault. Extended oil change intervals according to manufacturer's specifications

application notes

TIPP-OIL Excellence 5W-30 is ideally suited for energy-saving year-round use in modern passenger car petrol and diesel engines.

TIPP-OIL Excellence 5W-30 is used in Ford and Renault engines with the specified specifications. The operating instructions of the vehicle and engine manufacturers must be observed.

Quality Classification

specifications

ACEA A1/B1

ACEA A5/B5

Recommendation API SL/CF API SL/CF

Ford WSS-M2C913-D Renault RN700

Licensed: API SL



IPT International Petroleum Trading LTD  
Robert-Bosch-Strasse 12  
25335 Elmshorn  
Company registration number: HRB 13315 PI  
Sales tax identification number: DE313987910  
**E-mailaddress:** [contact@tippoil.com](mailto:contact@tippoil.com)  
**Website:** [www.tippoil.com](http://www.tippoil.com)  
Tel: +4923036728527

TIPP-OIL Excellence 5W-30 is proven in practice and tested in units with filling regulations:

Ford WSS-M2C913-A/B/C

STJLR 03.5003

Fiat 9.55535-N1

Iveco 18-1811 Classe S1/S2

#### Features & Benefits

Excellent cold start properties even at low temperatures

Fuel savings under all operating conditions

Very good detergent and dispersing properties

Neutrality towards sealing materials

Low evaporation tendency, thus low oil consumption

Extensive protection against wear, corrosion and foam formation

Extended oil change intervals protect natural resources

#### Technical characteristics

Properties Data Unit Test according to

kinematic viscosity at 40°C 58.5 MM<sup>2</sup>/S DIN ISO 51562-2

kinematic viscosity at 100°C 10.1 MM<sup>2</sup>/S DIN ISO 51562-2

viscosity index 162 DIN ISO 2909

appearance YELLOW visual

density at 15°C 851 KG/M<sup>3</sup> DIN EN ISO 12185

Pour Point -39 CELSIUS ASTM D 7346



IPT International Petroleum Trading LTD  
Robert-Bosch-Strasse 12  
25335 Elmshorn  
Company registration number: HRB 13315 PI  
Sales tax identification number: DE313987910  
**E-mailaddress:** [contact@tippoil.com](mailto:contact@tippoil.com)  
**Website:** [www.tippoil.com](http://www.tippoil.com)  
Tel: +4923036728527

All data given are approximate values and are subject to the usual production fluctuations.

To the best of our knowledge, all data correspond to the current state of knowledge and our development. We reserve the right to make changes. All references to DIN standards are for product description purposes only and do not constitute a guarantee. In the event of any problems, request technical advice.

04.07.2018 11:52:32

