



IPT International Petroleum Trading LTD
Robert-Bosch-Strasse 12
25335 Elmshorn
Company registration number: HRB 13315 PI
Sales tax identification number: DE313987910
E-mailaddress: contact@tippoil.com
Website: www.tippoil.com
Tel: +4923036728527

product certificate

TIPP-OIL Extra Ultimate 15W-40

Description of the

TIPP-OIL Extra Ultimate 15W-40 is a modern engine oil for passenger car gasoline and diesel engines with and without turbocharging and direct injection. Extended oil change intervals according to manufacturer's instructions.

TIPP-OIL Extra Ultimate 15W-40 is characterized by excellent cold start characteristics, minimization of

fuel consumption, friction and wear. TIPP-OIL Extra Ultimate 15W-40 is a reliable and heavy-duty engine oil.

Instructions for use

TIPP-OIL Extra Ultimate 15W-40 is ideally suited for year-round use in all modern passenger car petrol and diesel engines.

TIPP-OIL Extra Ultimate 15W-40 is used in engines with the specified specifications. The operating instructions of the vehicle and engine manufacturers must be observed.

Quality Classification

specifications

ACEA A3/B4

API SL/CF



IPT International Petroleum Trading LTD
Robert-Bosch-Strasse 12
25335 Elmshorn
Company registration number: HRB 13315 PI
Sales tax identification number: DE313987910
E-mailaddress: contact@tippoil.com
Website: www.tippoil.com
Tel: +4923036728527

TIPP-OIL Extra 15W-40 is proven in practice and tested in units with filling regulations:

MB 229.1 FIAT 9.55535-G2/D2

VW 501 01/505 00

Features & Benefits

Excellent cold start properties even at low temperatures

A very stable and excellent viscosity behaviour, shear stability

Fuel savings under all operating conditions

Very good detergent and dispersing properties

Neutrality towards sealing materials

Low evaporation tendency, thus low oil consumption

Extensive protection against wear, corrosion and foam formation.

Catalyst suitability

Extended oil change intervals protect natural resources

Technical characteristics

Properties Data Unit Test according to

kinematic viscosity at 40°C 100,7 MM²/S DIN ISO 51562-2

kinematic viscosity at 100°C 14.2 MM²/S DIN ISO 51562-2

viscosity index 144 DIN ISO 2909



IPT International Petroleum Trading LTD
Robert-Bosch-Strasse 12
25335 Elmshorn
Company registration number: HRB 13315 PI
Sales tax identification number: DE313987910
E-mailaddress: contact@tippoil.com
Website: www.tippoil.com
Tel: +4923036728527

visual appearance YELLOWBROWN

density at 15°C 872 KG/M³ DIN EN ISO 12185

Pour Point -36 CELSIUS ASTM D 7346

All data given are approximate values and are subject to the usual production fluctuations.

To the best of our knowledge, all data correspond to the current state of knowledge and our development. We reserve the right to make changes. All references to DIN standards are for product description purposes only and do not constitute a guarantee. In the event of any problems, request technical advice.

13.07.2018 02:00:17

