



IPT International Petroleum Trading LTD
Robert-Bosch-Strasse 12
25335 Elmshorn
Company registration number: HRB 13315 PI
Sales tax identification number: DE313987910
E-mailaddress: contact@tippoil.com
Website: www.tippoil.com
Tel: +4923036728527

product certificate

TIPP-OIL FD Excellence 0W-30

Description of the

TIPP-OIL FD Excellence 0W-30 is a synthetic low-SAPS low friction engine oil for passenger car diesel engines.

TIPP-OIL FD Excellence 0W-30 is characterized by excellent cold start properties, minimization of fuel consumption, friction and wear.

TIPP-OIL FD Excellence 0W-30 is an engine oil specially designed for the requirements of Ford diesel engines with diesel particulate filters.

TIPP-OIL FD Excellence 0W-30 achieves a high viscosity index through its formulation with special base oils.

Instructions for use

TIPP-OIL FD Excellence 0W-30 is ideally suited for energy-saving, year-round use in modern passenger car diesel engines.

TIPP-OIL FD Excellence 0W-30 is used in Ford engines with the specified specifications.

The operating instructions of the vehicle and engine manufacturers must be observed.

Quality Classification

specifications

ACEA C2



IPT International Petroleum Trading LTD
Robert-Bosch-Strasse 12
25335 Elmshorn
Company registration number: HRB 13315 PI
Sales tax identification number: DE313987910
E-mailaddress: contact@tippoil.com
Website: www.tippoil.com
Tel: +4923036728527

TIPP-OIL FD Excellence 0W-30 is proven in practice and tested in units with filling regulations:

Ford WSS-M2C950-A Fiat 9.55535-GS1/DS1

Jaguar Land Rover STJLR.03.5007

Features & Benefits

Excellent cold start properties even at low temperatures below -30°C

Fuel savings under all operating conditions

Neutrality towards sealing properties

Low evaporation tendency and therefore low oil consumption

Extensive protection against wear, corrosion and foam formation

Extended oil change intervals protect natural resources

Low SAPS = reduced sulfated ash, phosphorus and sulfur

Technical characteristics

Properties Data Unit Test according to

kinematic viscosity at 40°C 46.0 MM²/S DIN ISO 51562-2

kinematic viscosity at 100°C 9.8 MM²/S DIN ISO 51562-2

viscosity index 206 DIN ISO 2909

appearance YELLOW visual

density at 15°C 846 KG/M³ DIN EN ISO 12185

Pour Point -45 CELSIUS ASTM D 7346



IPT International Petroleum Trading LTD
Robert-Bosch-Strasse 12
25335 Elmshorn
Company registration number: HRB 13315 PI
Sales tax identification number: DE313987910
E-mailaddress: contact@tippoil.com
Website: www.tippoil.com
Tel: +4923036728527

All data given are approximate values and are subject to the usual production fluctuations.

To the best of our knowledge, all data correspond to the current state of knowledge and our development. We reserve the right to make changes. All references to DIN standards are for product description purposes only and do not constitute a guarantee. In the event of any problems, request technical advice.

23.07.2018 02:00:37

