



IPT International Petroleum Trading LTD
Robert-Bosch-Strasse 12
25335 Elmshorn
Company registration number: HRB 13315 PI
Sales tax identification number: DE313987910
E-mailaddress: contact@tippoil.com
Website: www.tippoil.com
Tel: +4923036728527

product certificate

TIPP-OIL FS Combi 10W-30

Description of the

TIPP-OIL FS Combi 10W-30 is a synthetic high-performance low-viscosity engine oil for passenger car petrol and diesel engines with and without turbocharging and direct injection. Extended oil change intervals according to manufacturer's instructions.

TIPP-OIL FS Combi 10W-30 is characterized by excellent cold start properties, minimization of fuel consumption, friction and wear. TIPP-OIL FS Combi 10W-30 is a reliable and heavy-duty engine oil.

Instructions for use

TIPP-OIL FS Combi 10W-30 is ideally suited for year-round use in all modern passenger car petrol and diesel engines.

TIPP-OIL FS Combi 10W-30 is used in engines with the specified specifications.

The operating instructions of the vehicle and engine manufacturers must be observed.

Quality Classification

specifications

API SL/CF ACEA A3/B4



IPT International Petroleum Trading LTD
Robert-Bosch-Strasse 12
25335 Elmshorn
Company registration number: HRB 13315 PI
Sales tax identification number: DE313987910
E-mailaddress: contact@tippoil.com
Website: www.tippoil.com
Tel: +4923036728527

TIPP-OIL FS Combi 10W-30 is proven in practice and tested in units with filling regulations:

MB 229.3/229.1 BMW Special Oil

VW 501 01/502 00/505 00

Features & Benefits

Excellent cold start properties even at low temperatures below -25°C

A very stable and excellent viscosity behaviour, shear stability

Fuel savings under all operating conditions

Very good detergent and dispersing properties

Neutrality towards sealing materials

Low evaporation tendency, thus low oil consumption

Extensive protection against wear, corrosion and foam formation.

Catalyst suitability

Extended oil change intervals protect natural resources

Technical characteristics

Properties Data Unit Test according to

kinematic viscosity at 40°C 75.5 MM²/S DIN ISO 51562-2

kinematic viscosity at 100°C 11.6 MM²/S DIN ISO 51562-2

viscosity index 148 DIN ISO 2909

appearance YELLOW visual

density at 15°C 865 KG/M³ DIN EN ISO 12185

Pour Point -39 CELSIUS ASTM D 7346



IPT International Petroleum Trading LTD
Robert-Bosch-Strasse 12
25335 Elmshorn
Company registration number: HRB 13315 PI
Sales tax identification number: DE313987910
E-mailadress: contact@tippoil.com
Website: www.tippoil.com
Tel: +4923036728527

All data given are approximate values and are subject to the usual production fluctuations.

To the best of our knowledge, all data correspond to the current state of knowledge and our development. We reserve the right to make changes. All references to DIN standards are for product description purposes only and do not constitute a guarantee. In the event of any problems, request technical advice.

17.07.2018 02:01:02

