



IPT International Petroleum Trading LTD
Robert-Bosch-Strasse 12
25335 Elmshorn
Company registration number: HRB 13315 PI
Sales tax identification number: DE313987910
E-mailadress: contact@tippoil.com
Website: www.tippoil.com
Tel: +4923036728527

product certificate

TIPP-OIL FS Dura Fusion 5W-30

Description of the

TIPP-OIL FS Dura Fusion 5W-30 is a synthetic low SAPS fuel-efficient engine oil for passenger car gasoline and diesel engines. It is especially suitable for modern diesel engines with particulate filter.

TIPP-OIL FS Dura Fusion 5W-30 is characterized by excellent cold start properties, minimization of fuel consumption, friction and wear.

TIPP-OIL FS Dura Fusion 5W-30 helps to protect the environment. Extended oil change intervals according to manufacturer's instructions.

Instructions for use

TIPP-OIL FS Dura Fusion 5W-30 is a synthetic low-viscosity engine oil specially developed for diesel engines with particulate filters.

TIPP-OIL FS Dura Fusion 5W-30 is suitable for petrol and diesel engines in passenger cars and vans with and without turbochargers.

Quality Classification

specifications

ACEA C4

Recommended MB release 226.51 Renault RN0720

MB release 226.51 Renault RN0720



IPT International Petroleum Trading LTD
Robert-Bosch-Strasse 12
25335 Elmshorn
Company registration number: HRB 13315 PI
Sales tax identification number: DE313987910
E-mailaddress: contact@tippoil.com
Website: www.tippoil.com
Tel: +4923036728527

TIPP-OIL FS Dura Fusion 5W-30 is field-proven and tested in units with filling regulations:

MB 229.51/229.31 Fiat 9.55535-S4

Features & Benefits

Excellent cold start properties even at low temperatures below -30°C

The function of the hydraulic plungers is guaranteed at all temperatures.

Fuel savings under all operating conditions

A safe lubricating film at high operating temperatures

Neutrality towards sealing materials

Extensive protection against wear, corrosion and foam formation.

Low tendency to evaporation, thus low oil consumption.

Extended oil change intervals protect natural resources

Low SAPS = reduced sulfated ash, phosphorus and sulfur

Technical characteristics

Properties Data Unit Test according to

kinematic viscosity at 40°C 70.8 MM²/S DIN ISO 51562-2

kinematic viscosity at 100°C 11.9 MM²/S DIN ISO 51562-2

viscosity index 165 DIN ISO 2909

visual appearance YELLOWBROWN

density at 15°C 847 KG/M³ DIN EN ISO 12185

Pour Point -39 °C ASTM D 7346



IPT International Petroleum Trading LTD
Robert-Bosch-Strasse 12
25335 Elmshorn
Company registration number: HRB 13315 PI
Sales tax identification number: DE313987910
E-mailadress: contact@tippoil.com
Website: www.tippoil.com
Tel: +4923036728527

All data given are approximate values and are subject to the usual production fluctuations.

To the best of our knowledge, all data correspond to the current state of knowledge and our development. We reserve the right to make changes. All references to DIN standards are for product description purposes only and do not constitute a guarantee. In the event of any problems, request technical advice.

26.09.2018 02:00:08

