



IPT International Petroleum Trading LTD
Robert-Bosch-Strasse 12
25335 Elmshorn
Company registration number: HRB 13315 PI
Sales tax identification number: DE313987910
E-mailaddress: contact@tippoil.com
Website: www.tippoil.com
Tel: +4923036728527

product certificate

TIPP-OIL FS Elite 5W-40

Description of the

TIPP-OIL FS Elite 5W-40 is a synthetic low-viscosity engine oil for passenger car gasoline and diesel engines with and without turbocharging and direct injection.

TIPP-OIL FS Elite 5W-40 is characterized by excellent cold start properties, minimization of fuel consumption, friction and wear.

TIPP-OIL FS Elite 5W-40 offers maximum operational safety in all driving conditions, e.g. in extreme stop and go traffic in the city, as well as on high-speed motorway journeys.

Instructions for use

TIPP-OIL FS Elite 5W-40 is ideally suited for energy-saving year-round use in modern passenger car petrol and diesel engines.

Extended oil change intervals according to manufacturer's instructions. The operating instructions of the vehicle and engine manufacturers must be observed.

Quality Classification

specifications

ACEA A3/B4 API SN/CF

Recommendation:

Licensed: API SN MB release 229.5

TIPP-OIL FS Elite 5W-40 is proven in practice and tested in units with filling regulations:

BMW Longlife-01

MB 229.3/226.5



IPT International Petroleum Trading LTD
Robert-Bosch-Strasse 12
25335 Elmshorn
Company registration number: HRB 13315 PI
Sales tax identification number: DE313987910
E-mailaddress: contact@tippoil.com
Website: www.tippoil.com
Tel: +4923036728527

Porsche A40

Renault RN0700/0710

Chrysler MS-10725/12991

Fiat 9.55535-H2/M2/N2/Z2

Opel GM-LL-B-025

PSA B71 2296

VW 502 00/505 00

Features & Benefits

Excellent cold start properties even at low temperatures

Fuel savings under all operating conditions

Very good detergent and dispersing properties

Neutrality towards sealing materials

Low evaporation tendency, thus low oil consumption

Extensive protection against wear, corrosion and foam formation.

Extended oil change intervals protect natural resources

Technical characteristics

Properties Data Unit Test according to

kinematic viscosity at 40°C 84.1 MM²/S DIN ISO 51562-2

kinematic viscosity at 100°C 13.9 MM²/S DIN ISO 51562-2

viscosity index 171 DIN ISO 2909

appearance YELLOW visual



IPT International Petroleum Trading LTD
Robert-Bosch-Strasse 12
25335 Elmshorn
Company registration number: HRB 13315 PI
Sales tax identification number: DE313987910
E-mailaddress: contact@tippoil.com
Website: www.tippoil.com
Tel: +4923036728527

density at 15°C 850 KG/M³ DIN EN ISO 12185

Pour Point -42 CELSIUS ASTM D 7346

All data given are approximate values and are subject to the usual production fluctuations.

To the best of our knowledge, all data correspond to the current state of knowledge and our development. We reserve the right to make changes. All references to DIN standards are for product description purposes only and do not constitute a guarantee. In the event of any problems, request technical advice.

01.10.2018 02:00:00

