



IPT International Petroleum Trading LTD  
Robert-Bosch-Strasse 12  
25335 Elmshorn  
Company registration number: HRB 13315 PI  
Sales tax identification number: DE313987910  
**E-mailadress:** [contact@tippoil.com](mailto:contact@tippoil.com)  
**Website:** [www.tippoil.com](http://www.tippoil.com)  
Tel: +4923036728527

product certificate

TIPP-OIL FS Engine

FS engine is a synthetic 2-stroke oil based on synthetic base oils, selected 2-stroke additives and PIB content. It is characterised by high wear protection and reduced corrosion as well as prevention of deposits and glow ignitions. FS engine is ideally suited for air- and water-cooled 2-stroke engines, as well as for separate lubrication and self-mixing systems.

Application note:

FS engine is recommended for the lubrication of air-cooled 2-stroke petrol engines with high speed and under heavy load as well as for the lubrication of separate lubrication and self-mixing systems. FS engine is suitable for high-quality high-speed units such as brush cutters, leaf vacuums, chain saws etc. with over 6,000 rpm. Of course it is also suitable for scooters and the outboard area.

Specifications:

ISO-L-EGD, JASO FD

Tried and tested in practice in units with filling regulations:

Husqvarna, Piaggio Hexagon, Rotax, Stihl

Properties. High cleaning efficiency which the combustion chambers, as well as inlet and outlet channels of

High cleaning efficiency, which protects the combustion chambers, as well as the inlet and outlet ducts of

Keeps combustion residues and deposits free as far as possible



IPT International Petroleum Trading LTD  
Robert-Bosch-Strasse 12  
25335 Elmshorn  
Company registration number: HRB 13315 PI  
Sales tax identification number: DE313987910  
**E-mailaddress:** [contact@tippoil.com](mailto:contact@tippoil.com)  
**Website:** [www.tippoil.com](http://www.tippoil.com)  
Tel: +4923036728527

Clean spark plugs ensure optimum engine performance

Excellent lubrication of all engine parts

High wear and corrosion protection

Low exhaust pollution through high combustion

Properties Data Unit Test according to

Viscosity at 100°C 10,800 MM<sup>2</sup>/S DIN ISO 51562-2

Viscosity index 142 DIN ISO 2909

Colour Yellow visual

Density at 15°C 866.0 KG/M<sup>3</sup> DIN EN ISO 12185

Pourpoint -39 CELSIUS ASTM D 7346

All data given are approximate values and are subject to the usual production fluctuations.

To the best of our knowledge, all data correspond to the current state of knowledge and our development. We reserve the right to make changes. All references to DIN standards are for product description purposes only and do not constitute a guarantee. In case of any problems, please request technical advice.



IPT International Petroleum Trading LTD  
Robert-Bosch-Strasse 12  
25335 Elmshorn  
Company registration number: HRB 13315 PI  
Sales tax identification number: DE313987910  
**E-mailadress:** [contact@tippoil.com](mailto:contact@tippoil.com)  
**Website:** [www.tippoil.com](http://www.tippoil.com)  
Tel: +4923036728527

