



IPT International Petroleum Trading LTD  
Robert-Bosch-Strasse 12  
25335 Elmshorn  
Company registration number: HRB 13315 PI  
Sales tax identification number: DE313987910  
**E-mailaddress:** [contact@tippoil.com](mailto:contact@tippoil.com)  
**Website:** [www.tippoil.com](http://www.tippoil.com)  
Tel: +4923036728527

product certificate

TIPP-OIL FS Excellence 0W-40

Description of the

TIPP-OIL FS Excellence 0W-40 is a synthetic low-viscosity engine oil for passenger car gasoline and diesel engines with and without turbocharging and direct injection.

TIPP-OIL FS Excellence 0W-40 is characterized by excellent cold start properties, minimization of fuel consumption, friction and wear.

Extended oil change intervals according to manufacturer's specifications.

TIPP-OIL FS Excellence 0W-40 is a reliable and highly resilient engine oil developed to guarantee the low viscosity of SAE class 0W and at the same time low evaporation loss.

Instructions for use

TIPP-OIL FS Excellence 0W-40 is ideally suited for energy-saving year-round use in all modern passenger car petrol and diesel engines.

TIPP-OIL FS Excellence 0W-40 is used in engines with the specified specifications. The operating instructions of the vehicle and engine manufacturers must be observed.

Quality Classification

specifications

API SN/CF ACEA A3/B4

Licensed: Recommended

Licensed: API SN BMW Longlife-01



IPT International Petroleum Trading LTD  
Robert-Bosch-Strasse 12  
25335 Elmshorn  
Company registration number: HRB 13315 PI  
Sales tax identification number: DE313987910  
**E-mailaddress:** [contact@tippoil.com](mailto:contact@tippoil.com)  
**Website:** [www.tippoil.com](http://www.tippoil.com)  
Tel: +4923036728527

MB- 226.5 Porsche A40

MB- 229.5 VW 502 00/505 00

Renault RN0700/0710

TIPP-OIL FS Excellence 0W-40 is field-proven and tested in units with filling regulations:

Ford WSS-M2C937-A

MB 229.3

Fiat 9.55535-M2/Z2

PSA B71 2296

#### Features & Benefits

Excellent cold start properties even at low temperatures below -30°C

Extremely stable and excellent viscosity behavior, shear stability

Fuel savings under all operating conditions

Very good detergent and dispersing properties

Neutrality towards sealing materials

Low evaporation tendency, thus low oil consumption

Excellent protection against wear, corrosion and foam formation.

Catalyst suitability

Extended oil change intervals protect natural resources



IPT International Petroleum Trading LTD  
Robert-Bosch-Strasse 12  
25335 Elmshorn  
Company registration number: HRB 13315 PI  
Sales tax identification number: DE313987910  
**E-mailaddress:** [contact@tippoil.com](mailto:contact@tippoil.com)  
**Website:** [www.tippoil.com](http://www.tippoil.com)  
Tel: +4923036728527

#### Technical characteristics

Properties Data Unit Test according to

kinematic viscosity at 40°C 76.3 MM<sup>2</sup>/S DIN ISO 51562-2

kinematic viscosity at 100°C 13.5 MM<sup>2</sup>/S DIN ISO 51562-2

viscosity index 183 DIN ISO 2909

visual appearance YELLOWBROWN

density at 15°C 844 KG/M<sup>3</sup> DIN EN ISO 12185

Pour Point -54 °C ASTM D 7346

All data given are approximate values and are subject to the usual production fluctuations.

To the best of our knowledge, all data correspond to the current state of knowledge and our development. We reserve the right to make changes. All references to DIN standards are for product description purposes only and do not constitute a guarantee. In the event of any problems, request technical advice.

26.09.2018 02:00:06

