



IPT International Petroleum Trading LTD  
Robert-Bosch-Strasse 12  
25335 Elmshorn  
Company registration number: HRB 13315 PI  
Sales tax identification number: DE313987910  
**E-mailaddress:** [contact@tippoil.com](mailto:contact@tippoil.com)  
**Website:** [www.tippoil.com](http://www.tippoil.com)  
Tel: +4923036728527

product certificate

TIPP-OIL FS Racing 10W-60

Description of the

TIPP-OIL FS Racing 10W-60 is a high alloy synthetic low friction multi-grade engine oil based on specially selected base oils. TIPP-OIL FS Racing 10W-60 is also suitable for extremely sporty driving due to its special additive.

TIPP-OIL FS Racing 10W-60 is ideally suited for modern petrol engines under the heaviest load in car racing.

TIPP-OIL FS Racing 10W-60 ensures an optimum lubricating layer even at very high operating temperatures.

Instructions for use

TIPP-OIL FS Racing 10W-60 can be used as a special oil for car racing even under the toughest conditions.

Quality Classification

specifications

API SN/CF ACEA A3/B4

TIPP-OIL FS Racing 10W-60 is field-proven and tested in units with filling regulations:

MB 229.1 BMW M Series

VW 501 00/505 00 FIAT 9.55535-H3



IPT International Petroleum Trading LTD  
Robert-Bosch-Strasse 12  
25335 Elmshorn  
Company registration number: HRB 13315 PI  
Sales tax identification number: DE313987910  
**E-mailaddress:** [contact@tippoil.com](mailto:contact@tippoil.com)  
**Website:** [www.tippoil.com](http://www.tippoil.com)  
Tel: +4923036728527

#### Features & Benefits

Good fuel savings in partial and full load operation  
A very stable and excellent viscosity behaviour, shear stability  
Very good cold start properties  
Wear-protecting high oil film stability  
Safe lubricating layer even at very high operating temperatures  
Extensive protection against wear, corrosion and foam formation.  
Very good deterging and dispersing properties.  
Extended oil change intervals protect natural resources

#### Technical characteristics

Properties Data Unit Test according to  
kinematic viscosity at 40°C 160.1 MM<sup>2</sup>/S DIN ISO 51562-2  
kinematic viscosity at 100°C 23,1 MM<sup>2</sup>/S DIN ISO 51562-2  
viscosity index 174 DIN ISO 2909  
visual appearance YELLOWBROWN  
density at 15°C 855 KG/M<sup>3</sup> DIN EN ISO 12185  
Pour Point -39 °C ASTM D 7346

All data given are approximate values and are subject to the usual production fluctuations.

To the best of our knowledge, all data correspond to the current state of knowledge and our development. We reserve the right to make changes without notice. All references to DIN standards are for product description purposes only and do not constitute a guarantee. In the event of any problems, request technical advice.

04.07.2018 11:55:01



IPT International Petroleum Trading LTD  
Robert-Bosch-Strasse 12  
25335 Elmshorn  
Company registration number: HRB 13315 PI  
Sales tax identification number: DE313987910  
**E-mailadress:** [contact@tippoil.com](mailto:contact@tippoil.com)  
**Website:** [www.tippoil.com](http://www.tippoil.com)  
Tel: +4923036728527

