



IPT International Petroleum Trading LTD  
Robert-Bosch-Strasse 12  
25335 Elmshorn  
Company registration number: HRB 13315 PI  
Sales tax identification number: DE313987910  
**E-mailadress:** [contact@tippoil.com](mailto:contact@tippoil.com)  
**Website:** [www.tippoil.com](http://www.tippoil.com)  
Tel: +4923036728527

product certificate

TIPP-OIL FS Racing 5W-50

Description of the

TIPP-OIL FS Racing 5W-50 is a modern synthetic low friction multi-grade oil. TIPP-OIL FS Racing 5W-50 ensures an optimal lubricating layer even at very high operating temperatures.

TIPP-OIL FS Racing 5W-50 is ideally suited for modern petrol engines under the heaviest loads at car races.

TIPP-OIL FS Racing 5W-50 is also suitable for extremely sporty driving due to its special additive.

Instructions for use

TIPP-OIL FS Racing 5W-50 is suitable for an extremely sporty driving style. Safe lubricating layer even at very high operating temperatures.

TIPP-OIL FS Racing 5W-50 is used in engines with the specified specifications.

The operating instructions of the vehicle and engine manufacturers must be observed.

Quality Classification

specifications

ACEA A3/B4 API SN/CF



IPT International Petroleum Trading LTD  
Robert-Bosch-Strasse 12  
25335 Elmshorn  
Company registration number: HRB 13315 PI  
Sales tax identification number: DE313987910  
**E-mailaddress:** [contact@tippoil.com](mailto:contact@tippoil.com)  
**Website:** [www.tippoil.com](http://www.tippoil.com)  
Tel: +4923036728527

TIPP-OIL FS Racing 5W-50 is proven in practice and tested in units with filling regulations:

MB 229.3/229.1

Porsche A40 VW 501 01/505 00

#### Features & Benefits

A very stable and excellent viscosity behaviour, shear stability

Lower fuel consumption in partial and full load operation

Very good detergent and dispersing properties

Good shear stability

A reliable lubricating layer even at very high operating temperatures

Extensive protection against wear, corrosion and foam formation

Good cold start properties

Extended oil change intervals protect natural resources

#### Technical characteristics

Properties Data Unit Test according to

kinematic viscosity at 40°C 129.3 MM<sup>2</sup>/S DIN ISO 51562-2

kinematic viscosity at 100°C 20.4 MM<sup>2</sup>/S DIN ISO 51562-2

viscosity index 182 DIN ISO 2909

visual appearance YELLOWBROWN

density at 15°C 851 KG/M<sup>3</sup> DIN EN ISO 12185

Pour Point -39 CELSIUS ASTM D 7346



IPT International Petroleum Trading LTD  
Robert-Bosch-Strasse 12  
25335 Elmshorn  
Company registration number: HRB 13315 PI  
Sales tax identification number: DE313987910  
**E-mailaddress:** [contact@tippoil.com](mailto:contact@tippoil.com)  
**Website:** [www.tippoil.com](http://www.tippoil.com)  
Tel: +4923036728527

All data given are approximate values and are subject to the usual production fluctuations.

To the best of our knowledge, all data correspond to the current state of knowledge and our development. We reserve the right to make changes. All references to DIN standards are for product description purposes only and do not constitute a guarantee. In the event of any problems, request technical advice.

24.07.2018 02:00:13

