



IPT International Petroleum Trading LTD  
Robert-Bosch-Strasse 12  
25335 Elmshorn  
Company registration number: HRB 13315 PI  
Sales tax identification number: DE313987910  
**E-mailaddress:** [contact@tippoil.com](mailto:contact@tippoil.com)  
**Website:** [www.tippoil.com](http://www.tippoil.com)  
Tel: +4923036728527

product certificate

TIPP-OIL FS Racing Pro 15W-50

Description of the

TIPP-OIL FS Racing Pro 15W-50 is a modern synthetic multi-grade engine oil designed on the basis of particularly high-quality base oils.

TIPP-OIL FS Racing Pro 15W-50 is ideally suited for a sporty driving style due to its very high viscosity index and good shear stability.

TIPP-OIL FS Racing Pro 15W-50 is ideally suited for modern petrol engines under the heaviest load in car racing.

TIPP-OIL FS Racing Pro 15W-50 maintains a safe lubricating layer even at very high operating temperatures.

Instructions for use

TIPP-OIL FS Racing Pro 15W-50 can be used as a special oil for car racing even under the toughest conditions.

Quality Classification

specifications

ACEA A3/B4 API SN/CF

TIPP-OIL FS Racing Pro 15W-50 is field-proven and tested in units with filling regulations:

MB 229.3/229.1

PSA B71 2294/2300 VW 501 01/505 00



IPT International Petroleum Trading LTD  
Robert-Bosch-Strasse 12  
25335 Elmshorn  
Company registration number: HRB 13315 PI  
Sales tax identification number: DE313987910  
**E-mailaddress:** [contact@tippoil.com](mailto:contact@tippoil.com)  
**Website:** [www.tippoil.com](http://www.tippoil.com)  
Tel: +4923036728527

#### Features & Benefits

Excellent cold start properties  
Low friction loss  
Prevention of sludge formation  
A very stable and excellent viscosity behaviour, shear stability  
Low evaporation tendency, thus low oil consumption  
Extensive protection against wear, corrosion and foam formation.  
Extended oil change intervals protect natural resources

#### Technical characteristics

Properties Data Unit Test according to  
kinematic viscosity at 40°C 125.0 MM<sup>2</sup>/S DIN ISO 51562-2  
kinematic viscosity at 100°C 17.5 MM<sup>2</sup>/S DIN ISO 51562-2  
viscosity index 155 DIN ISO 2909  
visual appearance YELLOWBROWN  
density at 15°C 869 KG/M<sup>3</sup> DIN EN ISO 12185  
Pour Point -36 CELSIUS ASTM D 7346

All data given are approximate values and are subject to the usual production fluctuations.

To the best of our knowledge, all data correspond to the current state of knowledge and our development. We reserve the right to make changes. All references to DIN standards are for product description purposes only and do not constitute a guarantee. In the event of any problems, request technical advice.

23.07.2018 02:00:09



IPT International Petroleum Trading LTD  
Robert-Bosch-Strasse 12  
25335 Elmshorn  
Company registration number: HRB 13315 PI  
Sales tax identification number: DE313987910  
**E-mailaddress:** [contact@tippoil.com](mailto:contact@tippoil.com)  
**Website:** [www.tippoil.com](http://www.tippoil.com)  
Tel: +4923036728527

