



IPT International Petroleum Trading LTD  
Robert-Bosch-Strasse 12  
25335 Elmshorn  
Company registration number: HRB 13315 PI  
Sales tax identification number: DE313987910  
**E-mailaddress:** [contact@tippoil.com](mailto:contact@tippoil.com)  
**Website:** [www.tippoil.com](http://www.tippoil.com)  
Tel: +4923036728527

product certificate

TIPP-OIL FS Select 5W-30

Description of the

TIPP-OIL FS Select 5W-30 is a synthetic low-viscosity engine oil for passenger car gasoline and diesel engines with and without turbocharging and direct injection.

TIPP-OIL FS Select 5W-30 is characterized by excellent cold-start properties, minimization of friction and wear as well as lower fuel consumption. Extended oil change intervals according to manufacturer's instructions.

Instructions for use

TIPP-OIL FS Select 5W-30 is ideally suited for energy-saving year-round use in all modern passenger car petrol and diesel engines.

TIPP-OIL FS Select 5W-30 is used in engines with the specified specifications. The operating instructions of the vehicle and engine manufacturers must be observed.

Quality Classification

specifications

API SL/CF ACEA A3/B4

Recommended MB release 229.3 BMW Longlife-01

MB-Approval 229.3 BMW Longlife-01

MB release 229.5 VW 502 00/505 00



IPT International Petroleum Trading LTD  
Robert-Bosch-Strasse 12  
25335 Elmshorn  
Company registration number: HRB 13315 PI  
Sales tax identification number: DE313987910  
**E-mailaddress:** [contact@tippoil.com](mailto:contact@tippoil.com)  
**Website:** [www.tippoil.com](http://www.tippoil.com)  
Tel: +4923036728527

TIPP-OIL FS Select 5W-30 is proven in practice and tested in units with filling regulations:

MB 226.5 Opel GM-LL-A/B-025

Renault RN0700/0710

#### Features & Benefits

Excellent cold start properties even at low temperatures below -30°C

A very stable and excellent viscosity behaviour, shear stability

Fuel savings under all operating conditions

Very good detergent and dispersing properties

Neutrality towards sealing materials

Low evaporation tendency, thus low oil consumption

Excellent protection against wear, corrosion and foaming.

Catalyst suitability

Prevents clogging of the diesel soot filter

Extended oil change intervals protect natural resources

#### Technical characteristics

Properties Data Unit Test according to

kinematic viscosity at 40°C 72.4 MM<sup>2</sup>/S DIN ISO 51562-2

kinematic viscosity at 100°C 12.1 MM<sup>2</sup>/S DIN ISO 51562-2

viscosity index 165 DIN ISO 2909

visual appearance YELLOWBROWN



IPT International Petroleum Trading LTD  
Robert-Bosch-Strasse 12  
25335 Elmshorn  
Company registration number: HRB 13315 PI  
Sales tax identification number: DE313987910  
**E-mailadress:** [contact@tippoil.com](mailto:contact@tippoil.com)  
**Website:** [www.tippoil.com](http://www.tippoil.com)  
Tel: +4923036728527

density at 15°C 852 KG/M<sup>3</sup> DIN EN ISO 12185

Pour Point -42 CELSIUS ASTM D 7346

All data given are approximate values and are subject to the usual production fluctuations.

To the best of our knowledge, all data correspond to the current state of knowledge and our development. We reserve the right to make changes. All references to DIN standards are for product description purposes only and do not constitute a guarantee. In the event of any problems, request technical advice.

09.07.2018 02:00:29

