



IPT International Petroleum Trading LTD  
Robert-Bosch-Strasse 12  
25335 Elmshorn  
Company registration number: HRB 13315 PI  
Sales tax identification number: DE313987910  
**E-mailaddress:** [contact@tippoil.com](mailto:contact@tippoil.com)  
**Website:** [www.tippoil.com](http://www.tippoil.com)  
Tel: +4923036728527

product certificate

TIPP-OIL FS Spezial 20W-50

Description of the

TIPP-OIL FS Spezial 20W-50 is a high-alloy, synthetic low-viscosity multi-grade engine oil based on specially selected base oils. TIPP-OIL FS Spezial 20W-50 is also suitable for extremely sporty driving due to its special additive.

TIPP-OIL FS Spezial 20W-50 is ideally suited for modern petrol engines under the heaviest loads at car races. TIPP-OIL FS Spezial 20W-50 ensures an optimum lubricating layer even at very high operating temperatures.

Instructions for use

TIPP-OIL FS Spezial 20W-50 can be used as a special oil for car racing even under the most difficult conditions.

Quality Classification

specifications

ACEA A3/B4

API SN/CF



IPT International Petroleum Trading LTD  
Robert-Bosch-Strasse 12  
25335 Elmshorn  
Company registration number: HRB 13315 PI  
Sales tax identification number: DE313987910  
**E-mailaddress:** [contact@tippoil.com](mailto:contact@tippoil.com)  
**Website:** [www.tippoil.com](http://www.tippoil.com)  
Tel: +4923036728527

TIPP-OIL FS Spezial 20W-50 has been tried and tested in practice in units with filling regulations:

MB 229.1

VW 501 01/505 00

#### Features & Benefits

As a synthetic engine oil it can be used all year round.

A very stable and excellent viscosity behaviour, shear stability

Fuel savings through reduced friction loss

Wear-protecting high oil film stability

Continuous high oil pressure

Low evaporation tendency,

Extensive protection against wear, corrosion and foam formation.

Catalyst suitability

Prevention of black sludge formation

Extended oil change intervals protect natural resources

#### Technical characteristics

Properties Data Unit Test according to

kinematic viscosity at 40°C 123.0 MM<sup>2</sup>/S DIN ISO 51562-2

kinematic viscosity at 100°C 18.0 MM<sup>2</sup>/S DIN ISO 51562-2

viscosity index 164 DIN ISO 2909

visual appearance YELLOWBROWN



IPT International Petroleum Trading LTD  
Robert-Bosch-Strasse 12  
25335 Elmshorn  
Company registration number: HRB 13315 PI  
Sales tax identification number: DE313987910  
**E-mailadress:** [contact@tippoil.com](mailto:contact@tippoil.com)  
**Website:** [www.tippoil.com](http://www.tippoil.com)  
Tel: +4923036728527

density at 15°C 857 KG/M<sup>3</sup> DIN EN ISO 12185

Pour Point -39 CELSIUS ASTM D 7346

All data given are approximate values and are subject to the usual production fluctuations.

To the best of our knowledge, all data correspond to the current state of knowledge and our development. We reserve the right to make changes. All references to DIN standards are for product description purposes only and do not constitute a guarantee. In case of any problems, please request technical advice.

04.07.2018 11:55:04





IPT International Petroleum Trading LTD  
Robert-Bosch-Strasse 12  
25335 Elmshorn  
Company registration number: HRB 13315 PI  
Sales tax identification number: DE313987910  
**E-mailadress:** [contact@tippoil.com](mailto:contact@tippoil.com)  
**Website:** [www.tippoil.com](http://www.tippoil.com)  
Tel: +4923036728527

