



IPT International Petroleum Trading LTD
Robert-Bosch-Strasse 12
25335 Elmshorn
Company registration number: HRB 13315 PI
Sales tax identification number: DE313987910
E-mailaddress: contact@tippoil.com
Website: www.tippoil.com
Tel: +4923036728527

product certificate

TIPP-OIL FS Supreme 0W-20

Description of the

TIPP-OIL FS Supreme 0W-20 is a synthetic low-viscosity engine oil for petrol and diesel engines with and without turbocharging and direct injection.

TIPP-OIL FS Supreme 0W-20 is characterized by excellent cold start properties, minimization of fuel consumption, friction and wear. Extended oil change intervals according to manufacturer's instructions.

Instructions for use

TIPP-OIL FS Supreme 0W-20 is ideally suited for energy-saving year-round use in modern passenger car petrol and diesel engines. It reduces CO2 emissions and contributes to the protection of the environment.

TIPP-OIL FS Supreme 0W-20 is used in engines with the specified specifications. The operating instructions of the vehicle and engine manufacturers must be observed.

Quality Classification

specifications

ACEA A1/B1 API SN

Recommendation

MB- 229.71

MB- 229.71 Jaguar Land Rover STJLR.51.5122



IPT International Petroleum Trading LTD
Robert-Bosch-Strasse 12
25335 Elmshorn
Company registration number: HRB 13315 PI
Sales tax identification number: DE313987910
E-mailaddress: contact@tippoil.com
Website: www.tippoil.com
Tel: +4923036728527

TIPP-OIL FS Supreme 0W-20 is proven in practice and tested in units with filling regulations:

Properties

- Excellent cold start properties even at low temperatures
- Extremely stable and excellent viscosity behavior, shear stability
- Fuel savings under all operating conditions
- Very good detergent and dispersing properties
- Neutrality towards sealing materials
- Low evaporation tendency, thus low oil consumption
- Excellent protection against wear, corrosion and foam formation
- Extended oil change intervals protect natural resources

Technical characteristics

- Properties Data Unit Test according to
- kinematic viscosity at 40°C 40.1 MM²/S DIN ISO 51562-2
- kinematic viscosity at 100°C 8.2 MM²/S DIN ISO 51562-2
- viscosity index 183 DIN ISO 2909
- appearance yellowbrown visual
- density at 15°C 843 KG/M³ DIN EN ISO 12185
- pour point -45 CELSIUS ASTM D 7346



IPT International Petroleum Trading LTD
Robert-Bosch-Strasse 12
25335 Elmshorn
Company registration number: HRB 13315 PI
Sales tax identification number: DE313987910
E-mailaddress: contact@tippoil.com
Website: www.tippoil.com
Tel: +4923036728527

All data given are approximate values and are subject to the usual production fluctuations.

To the best of our knowledge, all data correspond to the current state of knowledge and our development. We reserve the right to make changes. All references to DIN standards are for product description purposes only and do not constitute a guarantee. In the event of any problems, request technical advice.

13.08.2018 10:41:30

