



IPT International Petroleum Trading LTD  
Robert-Bosch-Strasse 12  
25335 Elmshorn  
Company registration number: HRB 13315 PI  
Sales tax identification number: DE313987910  
**E-mailaddress:** [contact@tippoil.com](mailto:contact@tippoil.com)  
**Website:** [www.tippoil.com](http://www.tippoil.com)  
Tel: +4923036728527

product certificate

TIPP-OIL FS Supreme 10W-40

Description of the

TIPP-OIL FS Supreme 10W-40 is a synthetic high-performance low-viscosity engine oil for passenger car petrol and diesel engines with and without turbocharging and direct injection. Extended oil change intervals according to manufacturer's instructions.

TIPP-OIL FS Supreme 10W-40 is characterised by excellent cold start properties, minimisation of fuel consumption, friction, and a high level of oil resistance.

and wear and tear. With TIPP-OIL FS 10W-40, a reliable and heavy-duty engine oil has been developed.

Instructions for use

TIPP-OIL FS Supreme 10W-40 is ideally suited for year-round use in all modern passenger car petrol and diesel engines.

TIPP-OIL FS Supreme 10W-40 is used in engines with the specified specifications. The

Operating regulations of the motor vehicle and

Motor manufacturers must be observed.

Quality Classification

specifications

ACEA A3/B4 API SM/CF



IPT International Petroleum Trading LTD  
Robert-Bosch-Strasse 12  
25335 Elmshorn  
Company registration number: HRB 13315 PI  
Sales tax identification number: DE313987910  
**E-mailaddress:** [contact@tippoil.com](mailto:contact@tippoil.com)  
**Website:** [www.tippoil.com](http://www.tippoil.com)  
Tel: +4923036728527

TIPP-OIL FS Supreme 10W-40 is proven in practice and tested in units with filling regulations:

BMW Special Oil

MB 229.1

VW 501 01 / 505 00

VW 502 00 / 500 00

#### Features & Benefits

Excellent cold start properties even at low temperatures below -25°C

Very stable and excellent viscosity behaviour and shear stability

Fuel savings under all operating conditions

Very good detergent and dispersing properties

Neutrality towards sealing materials

Low evaporation tendency, thus low oil consumption

Extensive protection against wear, corrosion and foam formation.

Catalyst suitability

Extended oil change intervals protect natural resources

#### Technical characteristics

Properties Data Unit Test according to

kinematic viscosity at 100°C 13.480 MM<sup>2</sup>/S DIN ISO 51562-2

viscosity index 158 DIN ISO 2909



IPT International Petroleum Trading LTD  
Robert-Bosch-Strasse 12  
25335 Elmshorn  
Company registration number: HRB 13315 PI  
Sales tax identification number: DE313987910  
**E-mailaddress:** [contact@tippoil.com](mailto:contact@tippoil.com)  
**Website:** [www.tippoil.com](http://www.tippoil.com)  
Tel: +4923036728527

visual appearance YELLOWBROWN

density at 15°C 860,5 KG/M<sup>3</sup> DIN EN ISO 12185

Pour Point -39 CELSIUS ASTM D 7346

All data given are approximate values and are subject to the usual production fluctuations.

To the best of our knowledge, all data correspond to the current state of knowledge and our development. We reserve the right to make changes. All references to DIN standards are for product description purposes only and do not constitute a guarantee. In the event of any problems, request technical advice.

27.07.2018 02:00:12

