



IPT International Petroleum Trading LTD  
Robert-Bosch-Strasse 12  
25335 Elmshorn  
Company registration number: HRB 13315 PI  
Sales tax identification number: DE313987910  
**E-mailadress:** [contact@tippoil.com](mailto:contact@tippoil.com)  
**Website:** [www.tippoil.com](http://www.tippoil.com)  
Tel: +4923036728527

product certificate

TIPP-OIL FS Supreme 5W-20

Description of the

TIPP-OIL FS Supreme 5W-20 is a synthetic low-viscosity engine oil for passenger car gasoline and diesel engines with and without turbocharging and direct injection.

TIPP-OIL FS Supreme 5W-20 is characterized by excellent cold start properties, minimization of fuel consumption, friction and wear.

TIPP-OIL FS Supreme 5W-20 contributes to the protection of the environment by significantly reducing fuel consumption and emissions.

Instructions for use

TIPP-OIL FS Supreme 5W-20 is ideally suited for energy-saving year-round use in all modern passenger car petrol and diesel engines.

Quality Classification

specifications

ILSAC GF-5 API SN (RC)

TIPP-OIL FS Supreme 5W-20 is proven in practice and tested in units with filling regulations:

Fiat 9.55535-CR1

Ford WSS-M2C930-A

Chrysler MS-6395

GM 6094M



IPT International Petroleum Trading LTD  
Robert-Bosch-Strasse 12  
25335 Elmshorn  
Company registration number: HRB 13315 PI  
Sales tax identification number: DE313987910  
**E-mailadress:** [contact@tippoil.com](mailto:contact@tippoil.com)  
**Website:** [www.tippoil.com](http://www.tippoil.com)  
Tel: +4923036728527

Ford WSS-M2C945-A

#### Features & Benefits

Excellent cold start properties even at low temperatures

Fuel savings under all operating conditions

Very good detergent and dispersing properties

Neutrality towards sealing materials

Low evaporation tendency, thus low oil consumption

Extensive protection against wear, corrosion and foam formation.

Extended oil change intervals protect natural resources

No oil-induced deposits in combustion chambers, in the piston ring zone and on valves

#### Technical characteristics

Properties Data Unit Test according to

kinematic viscosity at 40°C 47.8 MM<sup>2</sup>/S DIN ISO 51562-2

kinematic viscosity at 100°C 8.2 MM<sup>2</sup>/S DIN ISO 51562-2

viscosity index 147 DIN ISO 2909

visual appearance YELLOWBROWN

density at 15°C 856 KG/M<sup>3</sup> DIN EN ISO 12185

Pour Point -42 CELSIUS ASTM D 7346



IPT International Petroleum Trading LTD  
Robert-Bosch-Strasse 12  
25335 Elmshorn  
Company registration number: HRB 13315 PI  
Sales tax identification number: DE313987910  
**E-mailadress:** [contact@tippoil.com](mailto:contact@tippoil.com)  
**Website:** [www.tippoil.com](http://www.tippoil.com)  
Tel: +4923036728527

All data given are approximate values and are subject to the usual production fluctuations.

To the best of our knowledge, all data correspond to the current state of knowledge and our development. We reserve the right to make changes. All references to DIN standards are for product description purposes only and do not constitute a guarantee. In the event of any problems, request technical advice.

16.07.2018 02:00:03

