



IPT International Petroleum Trading LTD  
Robert-Bosch-Strasse 12  
25335 Elmshorn  
Company registration number: HRB 13315 PI  
Sales tax identification number: DE313987910  
**E-mailaddress:** [contact@tippoil.com](mailto:contact@tippoil.com)  
**Website:** [www.tippoil.com](http://www.tippoil.com)  
Tel: +4923036728527

product certificate

TIPP-OIL FS Ultra 0W-30

Description of the

TIPP-OIL FS Ultra 0W-30 is a synthetic low-viscosity engine oil for passenger car gasoline and diesel engines with and without turbocharging and direct injection.

TIPP-OIL FS Ultra 0W-30 is characterized by excellent cold start properties, minimization of fuel consumption, friction and wear. Extended oil change intervals according to manufacturer's instructions.

Instructions for use

TIPP-OIL FS Ultra 0W-30 is ideally suited for energy-saving year-round use in all modern passenger car petrol and diesel engines.

TIPP-OIL FS Ultra 0W-30 is used in engines with the specified specifications. The operating instructions of the vehicle and engine manufacturers must be observed.

Quality Classification

specifications

ACEA A5/B5 API SL/CF

TIPP-OIL FS Ultra 0W-30 is proven in practice and tested in units with filling regulations:

VW 503 00/506 00/506 01



IPT International Petroleum Trading LTD  
Robert-Bosch-Strasse 12  
25335 Elmshorn  
Company registration number: HRB 13315 PI  
Sales tax identification number: DE313987910  
**E-mailaddress:** [contact@tippoil.com](mailto:contact@tippoil.com)  
**Website:** [www.tippoil.com](http://www.tippoil.com)  
Tel: +4923036728527

#### Features & Benefits

Excellent cold start properties even at low temperatures below -30°C  
Extremely stable and excellent viscosity behavior, shear stability  
Fuel savings under all operating conditions  
Very good detergent and dispersing properties  
Neutrality towards sealing materials  
Low evaporation tendency, thus low oil consumption  
Excellent protection against wear, corrosion and foam formation.  
Catalyst suitability  
Extended oil change intervals protect natural resources

#### Technical characteristics

Properties Data Unit Test according to  
kinematic viscosity at 40°C 52,1 MM<sup>2</sup>/S DIN ISO 51562-2  
kinematic viscosity at 100°C 9.9 MM<sup>2</sup>/S DIN ISO 51562-2  
viscosity index 180 DIN ISO 2909  
appearance YELLOW visual  
density at 15°C 846 KG/M<sup>3</sup> DIN EN ISO 12185  
Pour Point -45 CELSIUS ASTM D 7346

All data given are approximate values and are subject to the usual production fluctuations.

To the best of our knowledge, all data correspond to the current state of knowledge and our development. We reserve the right to make changes. All references to DIN standards are for product description purposes only and do not constitute a guarantee. In the event of any problems, request technical advice.16.07.2018 02:00:05



IPT International Petroleum Trading LTD  
Robert-Bosch-Strasse 12  
25335 Elmshorn  
Company registration number: HRB 13315 PI  
Sales tax identification number: DE313987910  
**E-mailadress:** [contact@tippoil.com](mailto:contact@tippoil.com)  
**Website:** [www.tippoil.com](http://www.tippoil.com)  
Tel: +4923036728527

