



IPT International Petroleum Trading LTD  
Robert-Bosch-Strasse 12  
25335 Elmshorn  
Company registration number: HRB 13315 PI  
Sales tax identification number: DE313987910  
**E-mailadress:** [contact@tippoil.com](mailto:contact@tippoil.com)  
**Website:** [www.tippoil.com](http://www.tippoil.com)  
Tel: +4923036728527

product certificate

TIP-OIL FS VLV 0W-30

Description of the

TIPP-OIL FS VLV 0W-30 is a synthetic low-viscosity engine oil for passenger cars, petrol and diesel engines with and without turbocharging and direct injection. Minimization of friction, wear and fuel consumption, excellent cold start properties. Extended oil change intervals according to manufacturer's instructions.

The excellent cold-start behaviour ensures optimum lubrication reliability in the cold-running phase. Due to a significant fuel saving, the

TIPP-OIL FS VLV 0W-30 helps to protect the environment by reducing emissions.

Instructions for use

TIPP-OIL FS VLV 0W-30 is a universal, fuel-saving engine oil, a top product for petrol and diesel passenger car engines. Suitable for petrol and passenger car diesel engines with and without turbocharging as synthetic all-year engine oil.

Especially suitable for vehicles with filling regulation VCC 95200377.

Quality Classification

specifications

ACEA A5/B5 API SL/CF



IPT International Petroleum Trading LTD  
Robert-Bosch-Strasse 12  
25335 Elmshorn  
Company registration number: HRB 13315 PI  
Sales tax identification number: DE313987910  
**E-mailaddress:** [contact@tippoil.com](mailto:contact@tippoil.com)  
**Website:** [www.tippoil.com](http://www.tippoil.com)  
Tel: +4923036728527

TIPP-OIL FS VLV 0W-30 is proven in practice and tested in units with filling regulations:

VOLVO VCC 95200377 Ford WSS-M2C920-A

Renault RN0700/0710

#### Features & Benefits

Universal use in all modern petrol and diesel engines

Fast oiling of the engine, even at temperatures below -30°C

Low evaporation tendency, thus low oil consumption

Safety against sludge, coking, varnish and corrosion even with unfavourable conditions  
operating conditions

The function of the hydraulic plungers is guaranteed at all temperatures.

No oil-induced deposits in combustion chambers, in the piston ring zone and on valves

Unchanged viscosity during the entire oil change interval, high viscosity index

Neutrality towards sealing materials

Miscibility with all commercially available engine oils. Flushing runs are not necessary.

#### Technical characteristics

Properties Data Unit Test according to

kinematic viscosity at 40°C 53.0 MM<sup>2</sup>/S DIN ISO 51562-2

kinematic viscosity at 100°C 10.0 MM<sup>2</sup>/S DIN ISO 51562-2

viscosity index 181 DIN ISO 2909



IPT International Petroleum Trading LTD  
Robert-Bosch-Strasse 12  
25335 Elmshorn  
Company registration number: HRB 13315 PI  
Sales tax identification number: DE313987910  
**E-mailaddress:** [contact@tippoil.com](mailto:contact@tippoil.com)  
**Website:** [www.tippoil.com](http://www.tippoil.com)  
Tel: +4923036728527

appearance YELLOW visual

density at 15°C 848 KG/M<sup>3</sup> DIN EN ISO 12185

Pour Point -39 °C ASTM D 7346

All data given are approximate values and are subject to the usual production fluctuations.

To the best of our knowledge, all data correspond to the current state of knowledge and our development. We reserve the right to make changes. All references to DIN standards are for product description purposes only and do not constitute a guarantee. In the event of any problems, request technical advice.

23.07.2018 02:00:37

