



IPT International Petroleum Trading LTD
Robert-Bosch-Strasse 12
25335 Elmshorn
Company registration number: HRB 13315 PI
Sales tax identification number: DE313987910
E-mailaddress: contact@tippoil.com
Website: www.tippoil.com
Tel: +4923036728527

product certificate

TIPP-OIL HC Mega HC 0W-30

Description of the

TIPP-OIL HC Mega 0W-30 is a synthetic low-viscosity engine oil for passenger car petrol and diesel engines of light transporters and high-performance vehicles with and without turbochargers and direct injection. TIPP-OIL HC Mega 0W-30 guarantees high operational safety in all driving conditions such as extreme stop-and-go traffic and high-speed motorway travel.

Instructions for use

TIPP-OIL HC Mega 0W-30 is ideal for energy-saving year-round use in modern passenger car petrol and diesel engines.

TIPP-OIL HC Mega 0W-30 is suitable for extended oil change intervals and extends the service life of the particulate filter. The operating instructions of the vehicle and engine manufacturers must be observed.

Quality Classification

specifications

ACEA A3/B4 API SL/CF

TIPP-OIL HC Mega 0W-30 is proven in practice and tested in units with filling regulations:

BMW Longlife-01

MB 229.5/229.3

VW 502 00/505 00



IPT International Petroleum Trading LTD
Robert-Bosch-Strasse 12
25335 Elmshorn
Company registration number: HRB 13315 PI
Sales tax identification number: DE313987910
E-mailaddress: contact@tippoil.com
Website: www.tippoil.com
Tel: +4923036728527

Opel GM-LL-A/B-025

Renault RN0700/0710

Volvo VCC 95200356

Features & Benefits

A very stable and excellent viscosity behaviour, shear stability
Fuel savings through smooth-running properties
Long service life due to high oxidation stability
Prevention of black sludge formation
Low evaporation tendency, thus low oil consumption
Excellent protection against wear, corrosion and foam formation.
Catalyst suitability
Extended oil change intervals protect natural resources

Technical characteristics

Properties Data Unit Test according to
kinematic viscosity at 40°C 68.1 MM²/S DIN ISO 51562-2
kinematic viscosity at 100°C 12.2 MM²/S DIN ISO 51562-2
viscosity index 178 DIN ISO 2909
visual appearance YELLOWBROWN
density at 15°C 848 KG/M³ DIN EN ISO 12185
Pour Point -42 CELSIUS ASTM D 7346



IPT International Petroleum Trading LTD
Robert-Bosch-Strasse 12
25335 Elmshorn
Company registration number: HRB 13315 PI
Sales tax identification number: DE313987910
E-mailaddress: contact@tippoil.com
Website: www.tippoil.com
Tel: +4923036728527

All data given are approximate values and are subject to the usual production fluctuations.

To the best of our knowledge, all data correspond to the current state of knowledge and our development. We reserve the right to make changes. All references to DIN standards are for product description purposes only and do not constitute a guarantee. In the event of any problems, request technical advice.

13.07.2018 02:00:42

