



IPT International Petroleum Trading LTD  
Robert-Bosch-Strasse 12  
25335 Elmshorn  
Company registration number: HRB 13315 PI  
Sales tax identification number: DE313987910  
**E-mailaddress:** [contact@tippoil.com](mailto:contact@tippoil.com)  
**Website:** [www.tippoil.com](http://www.tippoil.com)  
Tel: +4923036728527

product certificate TIPP-OIL Hydraulic HVLP 32 Super Clear

#### Description of the

TIPP-OIL Hydraulic HVLP 32 Super Clear is a multi-grade hydraulic oil. Hydraulic HVLP 32 Super Clear offers high wear protection even under extreme loads due to effective additives. Hydraulic HVLP 32 Super Clear is characterized by good viscosity, temperature behaviour and reliable corrosion protection.

#### Application note:

Hydraulic HVLP 32 Super Clear is mainly used in hydraulic systems with strongly fluctuating operating temperatures. Hydraulic HVLP 32 Super Clear is ideally suited for heavy-duty hydraulic systems, earthmoving machinery and agricultural machinery. It is favoured for strongly fluctuating operating temperatures and must not be used for hydraulic systems containing silver or silver-plated construction and operating elements.

#### Specifications

Other specifications

#### Tried and tested in practice in units with filling regulations:

AFNOR 48 603 HV, CETOP RP 91H-HV, DENISON HF-1, HF-0, HF-2, General Motors LH-04-1, General Motors LH-06-1, General Motors LH-15-1, ISO 6743/4-HV, Sperry Vickers 1-286-S, Sperry Vickers M-2950-S, US Steel 127, US Steel 136



IPT International Petroleum Trading LTD  
Robert-Bosch-Strasse 12  
25335 Elmshorn  
Company registration number: HRB 13315 PI  
Sales tax identification number: DE313987910  
**E-mailaddress:** [contact@tippoil.com](mailto:contact@tippoil.com)  
**Website:** [www.tippoil.com](http://www.tippoil.com)  
Tel: +4923036728527

Properties:

Reliable protection against corrosion

Excellent wear protection

A stable viscosity index

Very good oxidation stability

Good air and water separation properties prevent the formation of foam

Very low yield point

Neutral to sealing materials

Properties Data Unit Test according to

kinematic viscosity at 40°C 29,800 MM<sup>2</sup>/S DIN ISO 51562-2

Viscosity index 162 DIN ISO 2909

Colour Yellow visual

Density at 15°C 854.0 KG/M<sup>3</sup> DIN EN ISO 12185

Pourpoint -45 CELSIUS ASTM D 7346

All data given are approximate values and are subject to the usual production fluctuations.

To the best of our knowledge, all data correspond to the current state of knowledge and our development. We reserve the right to make changes. All references to DIN standards are for product description purposes only and do not constitute a guarantee. In the event of any problems, request technical advice.



IPT International Petroleum Trading LTD  
Robert-Bosch-Strasse 12  
25335 Elmshorn  
Company registration number: HRB 13315 PI  
Sales tax identification number: DE313987910  
**E-mailaddress:** [contact@tippoil.com](mailto:contact@tippoil.com)  
**Website:** [www.tippoil.com](http://www.tippoil.com)  
Tel: +4923036728527

