



IPT International Petroleum Trading LTD  
Robert-Bosch-Strasse 12  
25335 Elmshorn  
Company registration number: HRB 13315 PI  
Sales tax identification number: DE313987910  
**E-mailaddress:** [contact@tippoil.com](mailto:contact@tippoil.com)  
**Website:** [www.tippoil.com](http://www.tippoil.com)  
Tel: +4923036728527

product certificate

TIPP-OIL LHC Supreme 0W-30

Description of the

TIPP-OIL LHC Supreme 0W-30 is a fully synthetic low-viscosity engine oil for passenger car gasoline and diesel engines of light transporters and high-performance vehicles with diesel particulate filter DPF and 3-way catalytic converter which require a minimum HTHS of 3.5 mPa\*s.

TIPP-OIL LHC Supreme 0W-30 is characterized by an excellent cold start behaviour and extends the service life of diesel particulate filters DPF and 3-way catalytic converter TCW by special additives. TIPP-OIL LHC Supreme 0W-30 achieves a high viscosity index due to its formulation with special base oils.

Instructions for use

TIPP-OIL LHC Supreme 0W-30 is ideal for energy-saving year-round use in modern passenger car petrol and diesel engines.

TIPP-OIL LHC Supreme 0W-30 is suitable for extended oil change intervals and extends the service life of the particulate filter. The operating instructions of the vehicle and engine manufacturers must be observed.

Quality Classification

specifications

ACEA C2/C3



IPT International Petroleum Trading LTD  
Robert-Bosch-Strasse 12  
25335 Elmshorn  
Company registration number: HRB 13315 PI  
Sales tax identification number: DE313987910  
**E-mailaddress:** [contact@tippoil.com](mailto:contact@tippoil.com)  
**Website:** [www.tippoil.com](http://www.tippoil.com)  
Tel: +4923036728527

Recommendation. MB release 229.51

MB release 229.51

TIPP-OIL LHC Supreme 0W-30 is proven in practice and tested in units with filling regulations:

BMW Longlife-04

MB 229.31

dexos2

Renault RN0700/0710

VW 502 00/505 00/505 01

#### Features & Benefits

Excellent cold start properties even at low temperatures below -25°C

Extremely stable and excellent viscosity behavior, shear stability

Fuel savings under all operating conditions

Safe lubricating film at high operating temperatures

Neutrality towards sealing materials

Low evaporation tendency, thus low oil consumption

Excellent protection against wear, corrosion and foam formation.

Catalyst suitability

Extended oil change intervals protect natural resources



IPT International Petroleum Trading LTD  
Robert-Bosch-Strasse 12  
25335 Elmshorn  
Company registration number: HRB 13315 PI  
Sales tax identification number: DE313987910  
**E-mailaddress:** [contact@tippoil.com](mailto:contact@tippoil.com)  
**Website:** [www.tippoil.com](http://www.tippoil.com)  
Tel: +4923036728527

#### Technical characteristics

Properties Data Unit Test according to

kinematic viscosity at 40°C 66.0 MM<sup>2</sup>/S DIN ISO 51562-2

kinematic viscosity at 100°C 11.9 MM<sup>2</sup>/S DIN ISO 51562-2

viscosity index 178 DIN ISO 2909

appearance YELLOW visual

density at 15°C 842 KG/M<sup>3</sup> DIN EN ISO 12185

Pour Point -60 CELSIUS ASTM D 7346

All data given are approximate values and are subject to the usual production fluctuations.

To the best of our knowledge, all data correspond to the current state of knowledge and our development. We reserve the right to make changes. All references to DIN standards are for product description purposes only and do not constitute a guarantee. In the event of any problems, request technical advice.

13.07.2018 02:00:44

