



IPT International Petroleum Trading LTD  
Robert-Bosch-Strasse 12  
25335 Elmshorn  
Company registration number: HRB 13315 PI  
Sales tax identification number: DE313987910  
**E-mailaddress:** [contact@tippoil.com](mailto:contact@tippoil.com)  
**Website:** [www.tippoil.com](http://www.tippoil.com)  
Tel: +4923036728527

product certificate

TIPP-OIL Low Premium 5W-30

Description of the

TIPP-OIL Low Premium 5W-30 is a synthetic Low SAPS fuel-efficient engine oil for gasoline and diesel passenger car engines with and without turbocharging and direct injection.

TIPP-OIL Low Premium 5W-30 is characterized by excellent cold start properties, minimization of fuel consumption, friction and wear.

TIPP-OIL Low Premium 5W-30 is a reliable and highly resilient engine oil developed to guarantee the low viscosity of SAPS Class 5W and low evaporation loss at the same time. Extended oil change intervals according to manufacturer's instructions.

Instructions for use

TIPP-OIL Low Premium 5W-30 is ideally suited for energy-saving year-round use in all modern passenger car petrol and diesel engines.

TIPP-OIL Low Premium 5W-30 is used in engines with the specified specifications. The operating instructions of the vehicle and engine manufacturers must be observed.

Quality Classification

specifications

ACEA C2/C3 API SN/CF

TIPP-OIL Low Premium 5W-30 is proven in practice and tested in units with filling regulations:

BMW Longlife-04

MB 229.52/229.51/229.31



IPT International Petroleum Trading LTD  
Robert-Bosch-Strasse 12  
25335 Elmshorn  
Company registration number: HRB 13315 PI  
Sales tax identification number: DE313987910  
**E-mailaddress:** [contact@tippoil.com](mailto:contact@tippoil.com)  
**Website:** [www.tippoil.com](http://www.tippoil.com)  
Tel: +4923036728527

Renault RN0700/0710

VW 502 00/505 00/505 01

Chrysler MS-11106 dexos2

Fiat 9.55535-S3

Ford WSS-M2C917-A

#### Features & Benefits

A very stable and excellent viscosity behaviour, shear stability

Fuel savings under all operating conditions

Very good detergent and dispersing properties

Neutrality towards sealing materials

Extensive protection against wear, corrosion and foam formation.

Catalyst suitability

Low evaporation tendency, thus low oil consumption

Extended oil change intervals protect natural resources

Very good cold start properties

Low SAPS = Low sulfate ash, phosphorus and sulfur content

#### Technical characteristics

Properties Data Unit Test according to

kinematic viscosity at 40°C 72.9 MM<sup>2</sup>/S DIN ISO 51562-2

kinematic viscosity at 100°C 12.2 MM<sup>2</sup>/S DIN ISO 51562-2

viscosity index 166 DIN ISO 2909



IPT International Petroleum Trading LTD  
Robert-Bosch-Strasse 12  
25335 Elmshorn  
Company registration number: HRB 13315 PI  
Sales tax identification number: DE313987910  
**E-mailaddress:** [contact@tippoil.com](mailto:contact@tippoil.com)  
**Website:** [www.tippoil.com](http://www.tippoil.com)  
Tel: +4923036728527

appearance YELLOW visual

density at 15°C 850 KG/M<sup>3</sup> DIN EN ISO 12185

Pour Point -39 °C ASTM D 7346

All data given are approximate values and are subject to the usual production fluctuations.

To the best of our knowledge, all data correspond to the current state of knowledge and our development. We reserve the right to make changes. All references to DIN standards are for product description purposes only and do not constitute a guarantee. In the event of any problems, request technical advice.

13.07.2018 02:00:35

