



IPT International Petroleum Trading LTD  
Robert-Bosch-Strasse 12  
25335 Elmshorn  
Company registration number: HRB 13315 PI  
Sales tax identification number: DE313987910  
**E-mailaddress:** [contact@tippoil.com](mailto:contact@tippoil.com)  
**Website:** [www.tippoil.com](http://www.tippoil.com)  
Tel: +4923036728527

product certificate

TIPP-OIL Mineral Super 30

Description of the

TIPP-OIL Mineral Super 30 is a mineral monograde oil for passenger car gasoline and diesel engines with and without turbocharging and commercial vehicle engines. Allows extended oil change intervals according to manufacturer's instructions.

TIPP-OIL Mineral Super 30 is a reliable and highly resilient engine oil.

Instructions for use

TIPP-OIL Mineral Super 30 is suitable for year-round use in petrol, diesel and commercial vehicle engines.

TIPP-OIL Mineral Super 30 is used in engines with the specified specifications. The operating instructions of the vehicle and engine manufacturers must be observed.

Quality Classification

Specifications API SF/CF

TIPP-OIL Mineral Super 30 is proven in practice and tested in units with filling regulations:

CCMC G4

MB 228.0/227.0

MIL-L-2104 D

MIL-L-46152 B



IPT International Petroleum Trading LTD  
Robert-Bosch-Strasse 12  
25335 Elmshorn  
Company registration number: HRB 13315 PI  
Sales tax identification number: DE313987910  
**E-mailaddress:** [contact@tippoil.com](mailto:contact@tippoil.com)  
**Website:** [www.tippoil.com](http://www.tippoil.com)  
Tel: +4923036728527

#### Features & Benefits

A stable and excellent viscosity behaviour  
Good detergent and dispersing properties  
Neutrality towards sealing materials  
Extensive protection against wear, corrosion and foam formation  
catalyst suitability  
Very good shear stability  
Prevention of black sludge formation  
High oxidation stability

#### Technical characteristics

Properties Data Unit Test according to  
kinematic viscosity at 40°C 94.5 MM<sup>2</sup>/S DIN ISO 51562-2  
kinematic viscosity at 100°C 11.6 MM<sup>2</sup>/S DIN ISO 51562-2  
viscosity index 112 DIN ISO 2909  
appearance brown visual  
density at 15°C 879 KG/M<sup>3</sup> DIN EN ISO 12185  
Pour Point -27 CELSIUS ASTM D 7346

All data given are approximate values and are subject to the usual production fluctuations.

To the best of our knowledge, all data correspond to the current state of knowledge and our development. We reserve the right to make changes. All references to DIN standards are for product description purposes only and do not constitute a guarantee. In the event of any problems, request technical advice.

27.07.2018 02:00:10



IPT International Petroleum Trading LTD  
Robert-Bosch-Strasse 12  
25335 Elmshorn  
Company registration number: HRB 13315 PI  
Sales tax identification number: DE313987910  
**E-mailaddress:** [contact@tippoil.com](mailto:contact@tippoil.com)  
**Website:** [www.tippoil.com](http://www.tippoil.com)  
Tel: +4923036728527

