



IPT International Petroleum Trading LTD
Robert-Bosch-Strasse 12
25335 Elmshorn
Company registration number: HRB 13315 PI
Sales tax identification number: DE313987910
E-mailaddress: contact@tippoil.com
Website: www.tippoil.com
Tel: +4923036728527

product certificate

TIPP-OIL Mineral Turbo 20W-50

Description of the

TIPP-OIL Mineral Turbo 20W-50 is a mineral multigrade engine oil for passenger car, petrol and diesel engines with and without turbocharging, as well as commercial vehicle engines.

Allows extended oil change intervals according to manufacturer's instructions.

TIPP-OIL Mineral Turbo 20W-50 is characterized by good cold start properties, minimization of fuel consumption, friction and wear.

TIPP-OIL Mineral Turbo 20W-50 is a reliable and heavy-duty engine oil.

Instructions for use

TIPP-OIL Mineral Turbo 20W-50 is suitable for year-round use in passenger car, petrol and diesel engines and commercial vehicle engines.

TIPP-OIL Mineral Turbo 20W-50 is used in engines with the specified specifications. The operating instructions of the vehicle and engine manufacture

TIPP-OIL Mineral Turbo 20W-50 is field-proven and tested in units with filling regulations:

Cummins CES 20071

Deutz DQC II-10

Mack EO-M

MAN 271



IPT International Petroleum Trading LTD
Robert-Bosch-Strasse 12
25335 Elmshorn
Company registration number: HRB 13315 PI
Sales tax identification number: DE313987910
E-mailaddress: contact@tippoil.com
Website: www.tippoil.com
Tel: +4923036728527

MB 228.1/229.1

MTU Type 1

Volvo VDS

VW 501 01/505 00

Features & Benefits

Good cold start properties even at low temperatures

A stable and excellent viscosity behaviour

Good detergent and dispersing properties

Neutrality towards sealing materials

Extensive protection against wear, corrosion and foam formation

catalyst suitability

Very good shear stability

Prevention of black sludge formation

High oxidation stability

Technical characteristics

Properties Data Unit Test according to

kinematic viscosity at 40°C 165.0 MM²/S DIN ISO 51562-2

kinematic viscosity at 100°C 18.9 MM²/S DIN ISO 51562-2

viscosity index 129 DIN ISO 2909

visual appearance YELLOWBROWN

density at 15°C 883 KG/M³ DIN EN ISO 12185

Pour Point -30 CELSIUS ASTM D 7346



IPT International Petroleum Trading LTD
Robert-Bosch-Strasse 12
25335 Elmshorn
Company registration number: HRB 13315 PI
Sales tax identification number: DE313987910
E-mailadress: contact@tippoil.com
Website: www.tippoil.com
Tel: +4923036728527

All data given are approximate values and are subject to the usual production fluctuations.

To the best of our knowledge, all data correspond to the current state of knowledge and our development. We reserve the right to make changes. All references to DIN standards are for product description purposes only and do not constitute a guarantee. In case of any problems, please request technical advice.

22.08.2018 02:00:22

