



IPT International Petroleum Trading LTD
Robert-Bosch-Strasse 12
25335 Elmshorn
Company registration number: HRB 13315 PI
Sales tax identification number: DE313987910
E-mailaddress: contact@tippoil.com
Website: www.tippoil.com
Tel: +4923036728527

product certificate

TIPP-OIL Outboard 10W-40 (blue)

Outboard 4-stroke 10W-40 is a semi-synthetic outboard 4-stroke engine oil based on selected base oils and special additives which ensure perfect lubrication and high wear protection. Outboard 4-stroke 10W-40 is particularly suitable for the lubrication of 4-stroke outboard engines with very high speeds and heavy loads. Outboard 4-stroke 10W-40 meets the requirements of the National Marine Manufacturers Association NMMA FC-W.

Application note:

Outboard 4-stroke 10W-40 is suitable for all FC-W oil recommended outboard engines. The operating instructions of the engine manufacturer must be observed. Outboard 4-stroke 10W-40 is particularly recommended for Mercury Verado, Tohatsu/Nissan, Johnson/Evinrude, Yamaha, Honda and Suzuki outboard engines. Outboard 4-stroke 10W-40 can also be used for seawater engines.

Specifications:

API SM, Honda, Johnson/Evinrude, NMMA FC-W, NMMA FC-W (CAT), Suzuki, Tohatsu/Nissan, Yamaha

Tried and tested in practice in units with filling regulations:

Mercury/Verado

Properties:

Perfect lubrication of all engine parts



IPT International Petroleum Trading LTD
Robert-Bosch-Strasse 12
25335 Elmshorn
Company registration number: HRB 13315 PI
Sales tax identification number: DE313987910
E-mailaddress: contact@tippoil.com
Website: www.tippoil.com
Tel: +4923036728527

Strong cleaning effect and residue-free combustion without deposits

Very high protection against wear, oxidation and corrosion

An adhesive, pressure and temperature resistant oil film

Strong cleaning effect and residue-free combustion without deposits

Excellent shear stability

Properties Data Unit Test according to

kinematic viscosity at 40°C 87.730 MM²/S DIN ISO 51562-2

Viscosity at 100°C 13.510 MM²/S DIN ISO 51562-2

Viscosity index 156 DIN ISO 2909

Color BLUE visual

Density at 15°C 857.1 KG/M³ DIN EN ISO 12185

Pourpoint -39 °C ASTM D 7346

All data given are approximate values and are subject to the usual production fluctuations.

To the best of our knowledge, all data correspond to the current state of knowledge and our development. We reserve the right to make changes. All references to DIN standards are for product description purposes only and do not constitute a guarantee. In case of any problems, please request technical advice.

22.08.2018 02:00:22



IPT International Petroleum Trading LTD
Robert-Bosch-Strasse 12
25335 Elmshorn
Company registration number: HRB 13315 PI
Sales tax identification number: DE313987910
E-mailaddress: contact@tippoil.com
Website: www.tippoil.com
Tel: +4923036728527

