



IPT International Petroleum Trading LTD
Robert-Bosch-Strasse 12
25335 Elmshorn
Company registration number: HRB 13315 PI
Sales tax identification number: DE313987910
E-mailadress: contact@tippoil.com
Website: www.tippoil.com
Tel: +4923036728527

product certificate TIPP-OIL PSF Premium Synthetic

Description of the

TIPP-OIL PSF Premium Synthetic is used for power steering systems in passenger cars and commercial vehicles as well as for the

Application in special vehicles intended. It is used with GRP IV & GRP V base oils.

(PAO & Ester) and a high-performance additive package containing anti-wear components, rust and oxidation inhibitors and defoaming additives. The product offers a highly effective wear protection and stability of the viscosity properties during long work under high load.

Instructions for use

TIPP-OIL PSF Premium Synthetic is intended for use in hydraulic power steering systems in passenger cars, SUVs and light commercial vehicles that require the use of DEXRON, DEXRON II or DEXRON III type fluids.

Before using this product, make sure that it complies with the OEM recommendation for the equipment's operating conditions and the customer's maintenance practices.

Quality Classification

specifications

TIPP-OIL PSF Premium Synthetic is proven in practice and tested in units with filling regulations:

AUDI: G 004 000, P/N G002000, P/N G002012

Chrysler: MS-1872, MS-5391, MS-9602, MS-11655



IPT International Petroleum Trading LTD
Robert-Bosch-Strasse 12
25335 Elmshorn
Company registration number: HRB 13315 PI
Sales tax identification number: DE313987910
E-mailaddress: contact@tippoil.com
Website: www.tippoil.com
Tel: +4923036728527

Ford: M2C-195A, M2C-204A

GM 88901975, 89021184, 9985010, 9985835

Hyundai PSF-3, PSF-4, 00232-19017

MAN 3289

MB 236.3, 345.0

Nissan PSF-II

Opel B 040 2012

Saab 93160548, 30 09 800, 30 32 380

Subaru K0209A0080

Toyota Type EH 008886-01

Volkswagen TL 52 146, P/N G002000, P/N G002012

Volvo 30741424, P/N 1161529

Mitsubishi PS FLUID, DIAMOND SP III

Features & Benefits

Protects pumps, hoses and seals from premature aging

Stability of viscosity properties

protects rubber and neoprene against loss of elasticity

Extended liquid life of 50,000 km



IPT International Petroleum Trading LTD
Robert-Bosch-Strasse 12
25335 Elmshorn
Company registration number: HRB 13315 PI
Sales tax identification number: DE313987910
E-mailaddress: contact@tippoil.com
Website: www.tippoil.com
Tel: +4923036728527

Technical characteristics

Properties Data Unit Test according to

kinematic viscosity at 40°C 28,9 MM²/S DIN ISO 51562-2

kinematic viscosity at 100°C 6.6 MM²/S DIN ISO 51562-2

viscosity index 194 DIN ISO 2909

appearance YELLOW visual

density at 15°C 836,5 KG/M³ DIN EN ISO 12185

Pour Point -72 °C ASTM D 7346

All data given are approximate values and are subject to the usual production fluctuations.

To the best of our knowledge, all data correspond to the current state of knowledge and our development. We reserve the right to make changes. All references to DIN standards are for product description purposes only and do not constitute a guarantee. In the event of any problems, request technical advice.

18.09.2018 02:00:07



IPT International Petroleum Trading LTD
Robert-Bosch-Strasse 12
25335 Elmshorn
Company registration number: HRB 13315 PI
Sales tax identification number: DE313987910
E-mailadress: contact@tippoil.com
Website: www.tippoil.com
Tel: +4923036728527

