



IPT International Petroleum Trading LTD  
Robert-Bosch-Strasse 12  
25335 Elmshorn  
Company registration number: HRB 13315 PI  
Sales tax identification number: DE313987910  
**E-mailaddress:** [contact@tippoil.com](mailto:contact@tippoil.com)  
**Website:** [www.tippoil.com](http://www.tippoil.com)  
Tel: +4923036728527

product certificate

TIPP-OIL Premium LL-12 Fuel 0W-30

Description of the

TIPP-OIL Premium LL-12 Fuel 0W-30 is a synthetic Mid SAPS oil for gasoline and diesel engines with and without turbocharging.

TIPP-OIL Premium LL-12 Fuel 0W-30 offers considerable fuel savings due to its special formulation, protects the turbocharger from deposits and thus enables maximum performance.

Instructions for use

TIPP-OIL Premium LL-12 Fuel 0W-30 is a fuel-saving oil and suitable for year-round use, especially for new BMW petrol and diesel engines.

TIPP-OIL Premium LL-12 Fuel 0W-30 is suitable for extended oil change intervals. The operating instructions of the vehicle and engine manufacturers must be observed.

Quality Classification

specifications

ACEA C2

TIPP-OIL Premium LL-12 Fuel 0W-30 is field-proven and tested in units with filling regulations:

BMW Longlife-12 FE



IPT International Petroleum Trading LTD  
Robert-Bosch-Strasse 12  
25335 Elmshorn  
Company registration number: HRB 13315 PI  
Sales tax identification number: DE313987910  
**E-mailaddress:** [contact@tippoil.com](mailto:contact@tippoil.com)  
**Website:** [www.tippoil.com](http://www.tippoil.com)  
Tel: +4923036728527

#### Features & Benefits

Excellent cleaning and dispersing properties  
Excellent protection against wear, corrosion and foaming.  
Constant oil layer density at different temperatures and pressures.  
Excellent fuel economy under all operating conditions  
very good cold start properties

#### Technical characteristics

Properties Data Unit Test according to  
kinematic viscosity at 40°C 54.4 MM<sup>2</sup>/S DIN ISO 51562-2  
kinematic viscosity at 100°C 10.1 MM<sup>2</sup>/S DIN ISO 51562-2  
viscosity index 175 DIN ISO 2909  
appearance YELLOW visual  
density at 15°C 846 KG/M<sup>3</sup> DIN EN ISO 12185  
Pour Point -45 CELSIUS ASTM D 7346

All data given are approximate values and are subject to the usual production fluctuations.

To the best of our knowledge, all data correspond to the current state of knowledge and our development. We reserve the right to make changes. All references to DIN standards are for product description purposes only and do not constitute a guarantee. In case of any problems, please request technical advice.

23.07.2018 02:00:48



IPT International Petroleum Trading LTD  
Robert-Bosch-Strasse 12  
25335 Elmshorn  
Company registration number: HRB 13315 PI  
Sales tax identification number: DE313987910  
**E-mailadress:** [contact@tippoil.com](mailto:contact@tippoil.com)  
**Website:** [www.tippoil.com](http://www.tippoil.com)  
Tel: +4923036728527

