



IPT International Petroleum Trading LTD
Robert-Bosch-Strasse 12
25335 Elmshorn
Company registration number: HRB 13315 PI
Sales tax identification number: DE313987910
E-mailaddress: contact@tippoil.com
Website: www.tippoil.com
Tel: +4923036728527

product certificate

TIPP-OIL Premium UHPD 5W-30

Description of the

TIPP-OIL Premium UHPD 5W-30 is a low-viscosity engine oil for all diesel engines with and without turbocharging in trucks, buses and working machines. It has excellent flow properties even at low temperatures. The fast reaching of critical lubrication points provides for considerable

Wear reduction during the warm-up phase. Selected active ingredients guarantee the highest

Engine cleanliness even in short-haul traffic. TIPP-OIL Premium UHPD 5W-30 enables extended oil change intervals according to manufacturer's instructions and high wear protection with low oil and fuel consumption.

Instructions for use

TIPP-OIL Premium UHPD 5W-30 is ideally suited for use in mixed fleets. It is used in motors with the specified specifications. The operating instructions of the vehicle and engine manufacturers must be observed.

Quality Classification

specifications

API CI-4

ACEA E4/E7

Global DHD-1 JASO DH-1



IPT International Petroleum Trading LTD
Robert-Bosch-Strasse 12
25335 Elmshorn
Company registration number: HRB 13315 PI
Sales tax identification number: DE313987910
E-mailadress: contact@tippoil.com
Website: www.tippoil.com
Tel: +4923036728527

TIPP-OIL Premium UHPD 5W-30 is proven in practice and tested in units with filling regulations:

Caterpillar ECF-2

MAN 3377/3277

MB 228.5

MTU Type 3

VOLVO VDS-3

Cummins CES 20076/78

Deutz DQC IV-10

MACK EO-N/EO-M Plus

Renault RXD/RLD-2

Scania LDF

Features & Benefits

Reduced fuel consumption thanks to smooth-running characteristics

Fastest possible oiling after the start

Protection against mirror surface formation on cylinder webs

Reduction of exhaust particles

Protection against corrosion, sludge and adhesions

Environmentally friendly due to long oil change intervals



IPT International Petroleum Trading LTD
Robert-Bosch-Strasse 12
25335 Elmshorn
Company registration number: HRB 13315 PI
Sales tax identification number: DE313987910
E-mailaddress: contact@tippoil.com
Website: www.tippoil.com
Tel: +4923036728527

Technical characteristics

Properties Data Unit Test according to

kinematic viscosity at 40°C 71,100 MM²/S DIN ISO 51562-2

kinematic viscosity at 100°C 12,000 MM²/S DIN ISO 51562-2

viscosity index 168 DIN ISO 2909

appearance YELLOW visual

density at 15°C 854,0 KG/M³ DIN EN ISO 12185

Pour Point -45 °C ASTM D 7346

All data given are approximate values and are subject to the usual production fluctuations.

To the best of our knowledge, all data correspond to the current state of knowledge and our development. We reserve the right to make changes. All references to DIN standards are for product description purposes only and do not constitute a guarantee. In the event of problems, request technical advice.

19.10.2018 11:22:50

