



IPT International Petroleum Trading LTD
Robert-Bosch-Strasse 12
25335 Elmshorn
Company registration number: HRB 13315 PI
Sales tax identification number: DE313987910
E-mailaddress: contact@tippoil.com
Website: www.tippoil.com
Tel: +4923036728527

product certificate

TIPP-OIL Racing Ultimate 10W-60

Description of the

TIPP-OIL Racing Ultimate 10W-60 is a fully synthetic multi-grade engine oil based on specially selected base oils. Its high content of group V polyalpha-olefins makes it a very special engine oil which meets even the highest demands.

TIPP-OIL Racing Ultimate 10W-60 is also suitable for extremely sporty driving due to its special additive.

TIPP-OIL Racing Ultimate 10W-60 is ideally suited for modern petrol engines under the heaviest load during races.

TIPP-OIL Racing Ultimate 10W-60 ensures an optimal lubricating layer even at very high operating temperatures.

Instructions for use

TIPP-OIL Racing Ultimate 10W-60 has been specially developed for speedway racing and is thus a

Special oil can also be used under the heaviest conditions. Its particularly modern and high-quality basic components in combination with a carefully selected additive package prevent deposits on thermally highly stressed components.

Quality Classification

specifications

ACEA A3/B4 API SN/CF



IPT International Petroleum Trading LTD
Robert-Bosch-Strasse 12
25335 Elmshorn
Company registration number: HRB 13315 PI
Sales tax identification number: DE313987910
E-mailaddress: contact@tippoil.com
Website: www.tippoil.com
Tel: +4923036728527

TIPP-OIL Racing Ultimate 10W-60 is field-proven and tested in units with filling regulations:

-

Features & Benefits

An ultra-modern, fully synthetic engine oil for extreme racing use.

Very stable and excellent viscosity behaviour, shear stability

Wear-protecting high oil film stability

Continuous high oil pressure

Low evaporation tendency, thus low oil consumption

The highest possible protection against wear, corrosion and foam formation.

Catalyst suitability

Black sludge formation is prevented

Extended oil change intervals protect natural resources

Technical characteristics

Properties Data Unit Test according to

kinematic viscosity at 40°C 170,000 MM²/S DIN ISO 51562-2

kinematic viscosity at 100°C 25,100 MM²/S DIN ISO 51562-2

viscosity index 181 DIN ISO 2909

appearance YELLOW visual

viscosity CCS 5830 MPAS ASTM D 5293

density at 15°C 860,0 KG/M³ DIN EN ISO 12185

Pour Point -45 CELSIUS ASTM D 7346



IPT International Petroleum Trading LTD
Robert-Bosch-Strasse 12
25335 Elmshorn
Company registration number: HRB 13315 PI
Sales tax identification number: DE313987910
E-mailaddress: contact@tippoil.com
Website: www.tippoil.com
Tel: +4923036728527

All data given are approximate values and are subject to the usual production fluctuations.

To the best of our knowledge, all data correspond to the current state of knowledge and our development. We reserve the right to make changes without notice. All references to DIN standards are for product description purposes only and do not constitute a guarantee. In the event of any problems, request technical advice.

04.07.2018 11:54:57

