



IPT International Petroleum Trading LTD  
Robert-Bosch-Strasse 12  
25335 Elmshorn  
Company registration number: HRB 13315 PI  
Sales tax identification number: DE313987910  
**E-mailaddress:** [contact@tippoil.com](mailto:contact@tippoil.com)  
**Website:** [www.tippoil.com](http://www.tippoil.com)  
Tel: +4923036728527

product certificate

TIP-OIL STOU 10W-30

Description of the

TIPP-OIL STOU 10W-30 is a modern multi-purpose oil for agricultural machines, excavators and construction machinery.

TIPP-OIL STOU 10W-30 is manufactured from high-quality base oils and selected additives and can be used equally in engines, transmissions and hydraulic systems of modern agricultural machines.

Instructions for use

TIPP-OIL STOU 10W-30 is suitable for year-round use as engine oil for gasoline engines and naturally aspirated and turbocharged diesel engines, as transmission oil (including wet brakes) and as hydraulic oil in tractors and agricultural machinery.

TIPP-OIL STOU 10W-30 can also be used as compressor oil.

Quality Classification

specifications

ACEA E2

API CG-4/SF

API GL-4



IPT International Petroleum Trading LTD  
Robert-Bosch-Strasse 12  
25335 Elmshorn  
Company registration number: HRB 13315 PI  
Sales tax identification number: DE313987910  
**E-mailaddress:** [contact@tippoil.com](mailto:contact@tippoil.com)  
**Website:** [www.tippoil.com](http://www.tippoil.com)  
Tel: +4923036728527

TIPP-OIL STOU 10W-30 is proven in practice and tested in units with filling regulations:

Allison C4 Caterpillar TO-2

John Deere J27 Ford ESN-M2C 159B

Massey Ferguson M1139/M 1144/M 1145 MAN 270

MB 227.1/228.1/228.3 MIL-L-2104D

ZF TE ML 06A/06B/06D/07B

#### Features & Benefits

Excellent high pressure properties

High dispersing and deterging capacity

Protection against wear, corrosion and foam formation

High oxidation stability

A high and stable viscosity index

#### Technical characteristics

Properties Data Unit Test according to

kinematic viscosity at 40°C 75.5 MM<sup>2</sup>/S DIN ISO 51562-2

kinematic viscosity at 100°C 11.7 MM<sup>2</sup>/S DIN ISO 51562-2

viscosity index 148 DIN ISO 2909

visual appearance YELLOWBROWN

density at 15°C 869,4 KG/M<sup>3</sup> DIN EN ISO 12185

Pour Point -39 °C ASTM D 7346



IPT International Petroleum Trading LTD  
Robert-Bosch-Strasse 12  
25335 Elmshorn  
Company registration number: HRB 13315 PI  
Sales tax identification number: DE313987910  
**E-mailadress:** [contact@tippoil.com](mailto:contact@tippoil.com)  
**Website:** [www.tippoil.com](http://www.tippoil.com)  
Tel: +4923036728527

All data given are approximate values and are subject to the usual production fluctuations.

To the best of our knowledge, all data correspond to the current state of knowledge and our development. We reserve the right to make changes. All references to DIN standards are for product description purposes only and do not constitute a guarantee. In case of any problems, please request technical advice.

05.09.2018 02:00:10

